

## Photocontrol - Metal Stem Mount Thermal Photocontrol, 120 V

Item K4421M



### PRODUCT DESCRIPTION

These photocontrols install on standard outdoor light fixtures and electrical boxes with 1/2"-14 NPSM thread or 7/8" knock-out holes for dusk-to-dawn ON/OFF control of outdoor lighting.

### FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Delay feature prevents unwanted OFF switching
- ▶ Die-cast metal housing
- ▶ 1/2"-14 NPSM threaded stem
- ▶ Washer gasket and locking nut included
- ▶ #18 AWG, 9" wire leads

### APPLICATIONS

- ▶ Parking Lot Lighting
- ▶ Landscape Lighting
- ▶ Exterior Lighting
- ▶ Pedestrian Pathway Lighting
- ▶ Street Lighting

### TECHNICAL DATA

#### General

Model Number	K4421M
Description	Metal Stem Mount Thermal Photocontrol, 120 V
UPC Code	078275105997
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty	2-Year limited
Usage Environments	Outdoor
Photocontrol Type	Thermal
Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Stem Mount
Photocontrol Sensor Location	Side

#### Control Specifications

Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc

#### Dimensions

Product Height (in)	3
Product Height (mm)	76.2

Product Width (in)	1 9/16
Wire Lead Length (in)	9
Wire Size Max	#18 AWG

#### Material Specifications

Cover Color	Gray
Housing Material	Die-Cast Zinc

#### Load Ratings

Magnetic Ballast Range(s)	8.3 A, 1000 VA
Tungsten Range(s)	15 A, 1800 W

#### Electrical Specifications

Wiring Option	Wire leads
Input Voltage Range(s)	120 VAC, 50/60 Hz

#### Packaging

Shipping Weight (lbs)	0.309
Unit Carton Height (in)	5

#### Environmental Specifications


Temperature (operation)	-40°C..70°C
-------------------------	-------------

#### Standards and Certifications

UL Certification	UL
CSA Certification	cCSAus
Other Certifications and Compatibilities	CA Title 20
California Proposition 65	DEHP

---

## ACCESSORIES



22LG116  
Light Guard Accessory for K4100 Series, K4200 Series  
Thermal Photocontrols



K42-SW-A  
Swivel Arm Accessory for EK4136S, K4100 Series Stem  
Mount Photocontrols



6LV1352  
Light Shield Accessory for EK4036S, EK4436SM, K4000  
Series Button Photocontrols