



Bardon™
Washout half-stall 0.125–1.0 gpf urinal, rear spud
K-4991-ER

Features

- Washout urinal
- 3/4" (19 mm) rear spud
- 0.125 - 1.0 gpf (0.47 - 3.8 lpf)
- Will replace K-4904-ER

Material

- Vitreous china

Installation

- 14" (356 mm) extended rim

Recommended Products/Accessories

K-23726 Drain treatment
K-23725 Cast iron cleaner
K-4929 Waterless Urinal Maintenance Balls



ADA

CSA B651

Codes/Standards

ASME A112.19.2/CSA B45.1
DOE - Energy Policy Act 1992
EPA WaterSense®
California Energy Commission (CEC)
ADA
ICC/ANSI A117.1
CSA B651

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
-------	------	-------------



0	White
---	-------



Bardon™
Washout half-stall 0.125–1.0 gpf urinal, rear spud
K-4991-ER



Technical Information

All product dimensions are nominal.

Spud size: 3/4", Inlet, Rear
Min. Water per Flush: 0.125 gpf (0.5 lpf)
Max. Water per Flush: 1 gpf (3.8 lpf)

Designed for the above water use when installed with a water-saving flushometer.

Notes

Install this product according to the installation guide.

Refer to manufacturer's instructions and local codes for flushometer requirements.

ADA, CSA B651 compliant when installed to the specific requirements of these regulations.