# Geometric | K-13467

Touchless single-hole lavatory faucet with Insight™ sensor technology, DC-powered, 0.5 gpm

## Features

- 0.5 gpm (1.9 lpm) maximum flow rate
- Factory-set 30-second maximum continual run cycle
- Vandal-resistant aerator
- 24" (610 mm) flexible supply hose for easy installation
- Less temperature mixer
- Less drain
- Includes two AAA batteries



## Sustainability

WATER-SAVING DESIGN

## Available Colors/Finishes

***Color tiles intended for reference only.***

CP Polished Chrome



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
11-12-2026 02:03 - US-CA

## Codes/Standards

***ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.***

ADA | CSA B651 | OBC

ASME A112.18.1/CSA B125.1
NSF/ANSI/CAN 372
DOE - Energy Policy Act 1992
ADA
ICC/ANSI A117.1
CSA B651
OBC

## Technical Information

***All product dimensions are nominal.***

### Spout

Spout Reach: 5-5/16" (135 mm)

### Flow Rate

Faucet Flow Rate: 0.5 gpm (1.9 l/min)

## Valves

Included Valves: UltraGlide, Digital

## Material

- Brass

## Recommended Products/Accessories

- [object Object]23726 Drain treatment
- K-23723 Faucet cleaner

## Optional Products/Accessories

- 1101643 Cache Spray 0.5 Gpm
- 1139288 Cache Aerated, 1.0 Gpm
- 1139289 Cache Laminar, 1.0 Gpm
- 1139290 Cache Aerated, 1.5 Gpm
- 1100596 Cache Std, M24 X 1 Pca Laminar

## Technology

- Electronic Insight™ sensor technology for accurate and consistent activation

## Warranty


***See website for detailed warranty information.***

KOHLER® One-Year Limited Warranty



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
11-12-2026 02:03 - US-CA

THE BOLD LOOK OF KOHLER.




## Installation

- Single-hole mounting
- Above-counter battery and valve for easy installation and maintenance

## Installation Notes

***Install this product according to the installation instructions.***

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required.
The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.
The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).
The maximum height of the lip basin should be 3/4" (19 mm).
Product includes rosebud spray aerator. Other aerator styles are available.
ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
11-12-2026 02:03 - US-CA

THE BOLD LOOK OF KOHLER.