


Install video:
korky.com/3060

1) Adjust arrow to toilet setting on chart.

Toilet not listed? Adjust arrow to 1 & flush. If stronger flush needed, adjust arrow.

8 = more water
 1 = less water



2) Push onto pegs & attach chain with minimal slack.



Toilet/Model Inodoro/Modelo	Setting Graduación
American Standard®	
Actifresh™ (4191A)	5
Cadet® 3 (4021)	8
Cadet® 3 Flowise HET (2568, 4019, 4021, 4021N)	1
Clean™ (4000)	8
Edgemere™ (4519A)	3
Titan Elite™ (4117A)	5
AquaSource®	
blue flapper (98923)	1
white flapper (98923)	5
810485	5
Crane®	
SureFlush® (31242)	3
Delta®	
Corrente® (RP71179)	4
Prelude® (RP71192)	4
Riosa® (RP71191)	4
Riosa® Select (RP84502)	7
Eljer®	
Diplomat™ (4021)	8
Titan™ (141-0777)	1

Ferguson®	
PROFLO® HET (PF9400)	8
Gerber®	
Avalanche® (28-890)	2
Avalanche® HE (28-890)	8
Glacier Bay®	
N2428T	7
N2428RB	7
TQRS1NP4P1	6
173-239	1
331-725T	7
1002-109-308/N2442T	8
Jacuzzi®	
Era™ (BK37)	7
Espree™ (EZ36)	8
Lyndsay™ (SW08959, SW08969, SW09959)	7
Maxima™ (EZ37)	3
Perfecta™ (EZ33)	6
Prestige™ (GV80)	7
Kohler®	
Cimarron® (K-4634)	1++

Mansfield®	
Barrett™ (106)	6
Brentwood™ (3147)	1
Denali™ (3916)	5
Maverick™ (102)	3
Maverick™ 1.28 (112)	1
Protector™ (1386)	7
Summit™ ADA (386)	3**
Waverly™ 1.28 (3195)	4
Pegasus®	
Colonnade™ (152-143)	8
Westminster™ (164-146)	8
Project Source®	
T803	5
TOTO®	
Drake® (ST743)	6
EcoDrake® (743E)	1
Supreme™ (MS863113/MS864114)	8
Ultimate® (MS853113/MS854114)	8
Tuscany®	
Erie™ (Z58R16S19306)	8
Huron™ (Z59E16S19306)	8

++ For wider Kohler® Cimarron® flush valves, adjust mounting arms:



*Instrucciones especiales para válvulas de descarga más amplias de Kohler® Cimarron®, ajuste los brazos de montaje:

**Only for this MANSFIELD® toilet, black arm in packaging needed. Visit korky.com/3060



Solo para estos inodoro Mansfield®, instale el brazo negro. Visite korky.com/3060

If you do not know your toilet model, follow instructions below:

Si no sabe cuál es el modelo de su inodoro, siga las instrucciones que aparecen más adelante:

1 Install New Flapper



a) Turn off water supply. Flush.




b) Mark water level (M) with pencil when original flapper closes.



c) Remove old flapper. Install new flapper. Attach chain (C) to flush lever (FL) with minimal slack.




X Too much slack




X Too little slack

Mansfield® toilets only. If flush valve peg larger than other peg, install black arm.



small peg
petit taquet
espiga pequeña

large peg
grand taquet
espiga grande



2 Adjust New Flapper

a) Turn water on. Let tank fill completely.



b) Turn off water. Flush. If water level drops within 1/2" of pencil mark (M), flapper install complete. If not, proceed to next step.



c) If below pencil line, adjust band arrow (A) to lower number. If above pencil line, adjust band arrow to higher number. Repeat steps 2a - 2b.