

Product Specifications



1/4" x 4" Slotted Hex Washer Head Concrete Screw Anchor

Part Number 14H400
Category Number 4560
UPC 781002256489



Concrete Screws are tempered masonry screws designed for long lasting performance and superior holding strength. Due to their unique thread design, they are the ideal fastening solution for light to medium duty applications in concrete, brick, masonry block and wood base materials. They are manufactured with a gimlet point that taps it's own threads while drilling into the base material. Common applications for this fastener include the attachment of electrical boxes, light fixtures, and masonry base materials.

Physical Characteristics

| | |
|-----------------|----------------|
| Install Tool | IT1000 |
| Bit | IB2PC |
| Anchor Type | Concrete Screw |
| Drive Type | Hex/Slotted |
| Head Type | Hex |
| Point Type | Gimlet |
| Thread Type | High-Low |
| Bit Size | #2 |
| Hex Size | 5/16" |
| Anchor Diameter | 1/4" |
| Anchor Length | 4" |
| Thread Length | 4" |
| Material | Carbon Steel |
| Finish | Blue Xylan |
| Color | Blue |

Packaging Details

| | |
|----------------|----------------------|
| Included | Carbide Tipped Drill |
| Standard Qty | 100 |
| Sleeve Qty | 500 |
| Master Qty | 1000 |
| Price Per | 100 |
| Package Length | 5.75 |
| Package Width | 4.50 |
| Package Height | 3.00 |
| Net Weight | 0.036 |
| Package Weight | 3.60 |

Performance Data

| | |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Pre-Drill Size | 3/16" x 5-1/2" |
| Applications | Poured Concrete, Prestressed Concrete, Cinder Block, Brick, Mortar |
| Special Features | Designed for Close To Edge Fastening, Strong Grip, Corrosion Resistance, Case Hardened, Can be Loosened for Adjustment or Removal |
| Cement Type | Various PSI |

Certifications

| | |
|----------------|-----|
| RoHS Compliant | Yes |
|----------------|-----|