



Color :  White

UPC Code : 078477572580

Country Of Origin : China

DVS02-1LW

Decora Vacancy Motion Sensor Light Switch, Manual-On, 2A, Single Pole

Decora Vacancy Motion Sensor Light Switch. 180° PIR manual-on, automatic-off, single pole, 150W LED/CFL, 250W Incandescent/Halogen, 200VA Magnetic Low Voltage, 250VA Electronic Low Voltage, 2A Resistive, wallplate sold separately. Can be used to comply with 2019 California Title 24, Part 6 Vacancy Control Device Requirements – White

- CONVENIENT – Turns lights OFF automatically when room is vacant
- EASY TO INSTALL – Slim profile fits in most wallboxes
- FLEXIBLE – Can be installed with or without a neutral wire
- PRACTICAL – Perfect for bathrooms, hallways and kids' bedrooms

Technical Information

Product Features

Auto-ON/Auto-OFF : No

California Title 24 : Yes

Color : White

Coverage (Sq.Ft.) : 180°, 900 Sq. Ft

Grade : Residential

LED Color : Green and Red

Load Rating : 150W LED/CFL, 250W Incandescent/Halogen, 250VA ELV, 200VA MLV, 2A Resistive

Mounting Type : Wall Switch

Neutral : Optional

Pole : 1

Sensor Technology : Passive Infrared

Sensor Type : Vacancy

Standards and Certifications : CSA, FCC, Title 24

Style Name : Decora

Switch : Relay

Time Delay : 1M, 5M, 10M, 20M

Voltage : 120 VAC

Wallplate : Not Included

Warranty : 5-Year Limited

Wiring : Ground or Neutral Required

Features and Benefits

- Manual ON/Automatic OFF operation
- Controls LED, CFL, Incandescent, Halogen, Magnetic Low Voltage, Electronic Low Voltage
- Provides 180° Field-of-View, 900 sq. ft. of coverage
- Shallow design easily fits in the wallbox and can replace a single pole switch
- Leaded terminals for easier installation
- Can be connected to a Neutral wire if present in the wallbox, or connected to ground wire if no Neutral wire is present in the wallbox
- Interchangeable line and load wires
- Program settings without removing the wallplate or faceplate
- Low profile design blends in with walls for a discreet appearance
- Adjustable delayed OFF time which can be set for 1 minute, 5 minutes, 10 minutes or 20 minutes
- Adjustable Range (sensitivity) to fit various coverage areas
- Convenient push-button provides Manual OFF light switching at any time
- Can be used to comply with 2019 California Title 24, Part 6 Vacancy Control Device Requirements

- Color change kits are available
- Five-Year Limited warranty

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

