



# GUAC2-W

20A SmartlockPro® Self-Test GFCI Combination 24W(4.8A) Type A/C USB In-Wall Charger Outlet – White

20 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Tamper-Resistant, Self-Test SmartlockPro® Self-Test GFCI Combination Type A/C USB In-Wall Charger, Wire Leads, NEMA 5-20R, 24W (4.8 Amps), Type-A/C USB Chargers, screws and self-grounding clip included – White

Color :  White

UPC Code : 078477996119

Country Of Origin : China

NEMA :  5-20R

### Available Colors :



Black



Light Almond

- SAFE – Delivers continuous ground fault protection, automatically self-tests to ensure it can respond to a ground fault
- FAST CHARGING – Smart chip technology provides over 2X the charging power of other GFCI USB outlets for a faster charge
- CODE REQUIRED – Fulfill NEC® requirements anywhere GFCI protection is needed
- SIMPLE – Status indicator light provides simple, intuitive feedback
- INSTALL – Requires extra deep wallbox for installation

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage :** 1 HP

**Dielectric Voltage :**  
Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

**Temperature Rise :** Max 30C after 100 cycles OL at 150 percent rated current

### Environmental Specifications

**Flammability :** UL94, 5VA

**Grounding Wire :** Green ground wire

**Operating Temperature :** -10° C to 40°C

### Electrical Specifications

**Grounding :** Self-Grounding

**Operating Temperature :** -10° C to 40°C

**Ratings :** 15A - 125V, 4.8A @ 5V

**Temperature Rise :** Max 30C after 100 cycles OL at 150 percent rated current

**Voltage :** 125 VAC

### Material Specifications

**Body Material :** Thermoplastic

**Color :** White

**Cover Material :** Thermoplastic

**Face Material :** Thermoplastic

**Grade :** Residential /Commercial Specification Grade

**Line Contacts :** Brass Double Wipe .031 Thick

**Notes :** Wallplate not included

**Product ID :** Ratings are permanently marked on device

**Strap Material :** Galvanized Steel

**Terminal ID** : Green lead - GND. Line and load both have:  
Black lead - Hot, White lead - Neutral

**Yoke** : Zinc-Plated Steel

#### Mechanical Specifications

**Pole** : 2

**Tamper Resistant** : Yes

**Trip Level** : Class A, 5mA plus or minus 1mA

**Type** : GFCI/USB A/C Combination

**Voltage** : 125 VAC

**Wire** : 5

#### Product Features

**Amperage** : 20 A

**At Rated Voltage** : 1 HP

**Brand** : SmartlockPro

**Color** : White

**Feature** : Self-Test

**Flammability** : UL94, 5VA

**Grade** : Residential /Commercial Specification Grade

**Grounding** : Self-Grounding

**NEMA** : 5-20R

**Pole** : 2

**Product Type** : GFCI/Outlet /USB Combo

**Tamper Resistant** : Yes

**Termination** : Wire leads (12AWG)

**Trip Level** : Class A, 5mA plus or minus 1mA

**Type** : GFCI/USB A/C Combination

**Voltage** : 125 VAC

**Wallplate** : Not included

**Warranty** : 2-Year Limited

**Wire** : 5

#### Standards & Certifications

**ANSI** : Yes

**CSA C22.2 No. 42** : Yes

**CSA-C22.2 No. 144.1-06** : Yes

**FCC Part 15** : Class B

**Fed Spec WC-596** : No

**Listed** : cCSAus

**NOM** : Yes

**UL 1310** : Yes

**UL 498** : Yes

**Patents** \*

CA2427366	CA2515035
CA2621644	CA2624409
CA2677283	CA2730014
MX251584	MX269232
MX276626	MX302458
MX308495	MX344697
US10483066	US7355117
US7697252	US7737809
US7820909	US7868719
US8004804	US8242362
US8587914	US9053886
US9276393	

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

#### SPECIFICATION SUBMITTAL

<p>JOB NAME:</p> <input style="width: 90%; height: 20px;" type="text"/>	<p>CATALOG NUMBERS:</p> <table border="1" style="width: 100%;"> <tbody> <tr> <td style="width: 50%; height: 20px;"><input type="text"/></td> <td style="width: 50%; height: 20px;"><input type="text"/></td> </tr> <tr> <td style="width: 50%; height: 20px;"><input type="text"/></td> <td style="width: 50%; height: 20px;"><input type="text"/></td> </tr> </tbody> </table>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>				
<input type="text"/>	<input type="text"/>				
<p>JOB NUMBER:</p> <input style="width: 90%; height: 20px;" type="text"/>					

#### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

#### Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.