




Color :  Black

UPC Code : 078477979419

Country Of Origin : Mexico - Pending

NEMA :  5-15R

Available Colors :



T5635-E

30W (6A) USB Dual Type-C/C Power Delivery Wall Outlet
Charger with 15A Tamper-Resistant Outlet

15 Amp, 125 Volt, Decora Tamper-Resistant Outlet. NEMA 5-15R, 30W (6 Amps), Dual Type-C/C Power Delivery USB Chargers, Grounding, Side Wired & Back Wired - Black

- **POWERFUL** – 30W charge on a single port. Up to 2x the charging power with PD-enabled devices
- **INNOVATIVE** – USB Type-C or USB-C provides faster charging and is emerging as the standard port on many phones, tablets and laptops
- **ENHANCED SAFETY** – Overcurrent protection helps protect electronic devices from over charging/heating and tamper-resistant outlets prevent unwanted objects from being inserted into the outlets
- **FAST CHARGING** – Smart chip ensures each device gets the power level it needs to charge fast and efficiently

Technical Information

Electrical Specifications

Amperage : 15 A

Body Material : Thermoplastic

Color : Black

Cover Material : Thermoplastic

Grounding : Grounding

Horsepower Rating : 15A-1/2 HP

Ratings : 15A-125V

Strap Material : Steel

Voltage : 125 VAC

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -10° C to 40°C

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Back & Side

Torque Range : 14 – 18 in.-lbs

Material Specifications

Body Material : Thermoplastic

Color : Black

Cover Material : Thermoplastic

Grade : Residential /Commercial Specification Grade

Strap Material : Steel

Mechanical Specifications

Listed : cCSAus

NOM : 057

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Back & Side

Torque Range : 14 – 18 in.-lbs

Warranty : 2-Year Limited

Product Features

Amperage : 15 A

Standards & Certifications

FCC Part 15 : Class B

Brand : Decora	Listed : cCSAus
Color : Black	NOM : 057
Flammability : Rated V-0 per UL 94	UL 1310 : Yes
	UL 498 : Yes
Grade : Residential /Commercial Specification Grade	Warranty : 2-Year Limited
NEMA : 5-15R	
Operating Temperature : -10° C to 40°C	
Power Delivery : Yes	
Product Type : Outlet/USB Combo	
Type : 30W Type C/C with PD Duplex Receptacle	
Voltage : 125 VAC	
Wallplate : Not Included	

Features and Benefits

- Up to 30W charge when PD-enabled device connected to single port. Up to 15W charge per port (30W total) when both USB ports are connected to devices. Examples of maximum charging outputs are:
 - Single port connected to PD-enabled device: 15VDC@2A (30W) or 9VDC@3A (27W)
 - Single port connected to non-PD device: 5VDC@3A (15W)
 - Both ports connected to devices (PD or non-PD): 5VDC@3A each (up to 30W total)
- Charges most Type-C devices as well as Type A devices (adapter required)
- Shallowest profile on the market for ease of installation
- Smart chip recognizes and optimizes the charging requirements of individual devices
- Built-in overcurrent protection helps protect the electronics from receiving too much power, which can damage the device
- Internal thermo regulator prevents the electronics from overheating
- USB Ports tested to meet the industry requirement to withstand over 10,000 insertions
- Compatible with USB 3.1, 3.0, 2.0, 1.1 devices
- Type-C USB Ports enable cables to be inserted in either direction
- Tamper-Resistant improves child safety – built-in shutter prevents access by most non-rated/foreign objects
- Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates
- Ideal for residential and commercial applications including kitchens, bedrooms, home offices, college dormitories, airport lounges, hospitals, salons and spas, hotels, meeting rooms, cafes, restaurants and more

- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates. Wallplate sold separately
- No data transfer capability

Patents*

US8242362	CA2624409
US7355117	US7820909
US7868719	US8944859
US9543667	US9368982
CA2869845	US9496726
CA2677283	CA2621644
MX338817	

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.