

T5833-I

5.1A USB Type A/Type-C Wall Outlet Charger with 20A Tamper-Resistant Receptacles

Combination Duplex Receptacle/Outlet and USB Charger. 20 Amp, 125 Volt, Decora Tamper-Resistant Receptacle/Outlet, NEMA 5-20R. 5.1 Amps, 5VDC, 2.0 Type A and Type-C USB Chargers. Grounding, Side Wired & Back Wired - Ivory




Color :  Ivory

UPC Code : 078477841327

Country Of Origin : Mexico

NEMA :  5-20R

Available Colors :



- SMART – Built-in smart chip recognizes the individual device's charging requirement to optimize the charge
- POWERFUL – Two high-powered charging ports deliver a combined total of 5.1A charging current and 25+ watts of power
- CONVENIENT – No more searching for charging adapters! Upgrade your existing outlets so you can charge up to two USB powered electronics at once, leaving the outlets free for additional power needs
- EASY – USB-C has a reversible connector that can be easily inserted into the charging port in any direction

Technical Information

Electrical Specifications

Amperage : 20 A

Body Material : Thermoplastic

Color : Ivory

Cover Material : Thermoplastic

Grounding : Grounding

Horsepower Rating : 20A-1/2 HP

Ratings : 20A-125V

Strap Material : Steel

Voltage : 125 VAC

Material Specifications

Body Material : Thermoplastic

Color : Ivory

Cover Material : Thermoplastic

Grade : Residential /Commercial Specification Grade

Strap Material : Steel

Product Features

Amperage : 20 A

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -10° C to 40°C

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Back & Side

Torque Range : 14 – 18 in.-lbs

Mechanical Specifications

Listed : cCSAus

NOM : 057

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Back & Side

Torque Range : 14 – 18 in.-lbs

Warranty : 2-Year Limited

Standards & Certifications

FCC Part 15 : Class B

Brand : Decora
Color : Ivory
Flammability : Rated V-0 per UL 94
Grade : Residential /Commercial Specification Grade
NEMA : 5-20R
Operating Temperature : -10° C to 40°C
Product Type : Outlet/USB Combo
Type : Type A/C Duplex Receptacle
Voltage : 125 VAC
Wallplate : Not Included

Listed : cCSAus
NOM : 057
UL 1310 : Yes
UL 498 : Yes
Warranty : 2-Year Limited

Features and Benefits

- Ideal for residential and commercial applications including kitchens, bedrooms, home offices, college dormitories, airport lounges, hospitals, salons and spas, hotels, meeting rooms, cafes, restaurants and more
- Smart chip technology recognizes and optimizes the charging requirements of individual devices including Apple, Samsung, Nexus, Pixel and more
- Tamper-Resistant improves child safety – built-in shutter prevents access by most non-rated/foreign objects
- USB Ports tested to withstand over 10,000 insertions
- Charges most Type A and Type-C USB powered devices
- Type-C Port permits the cables to be inserted easily in either direction
- Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates
- Compatible with USB 3.1, 3.0, 2.0, 1.1 devices
- No data transfer capability
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates. Wallplate sold separately

Patents *

US8242362	CA2624409
US7355117	US7820909
US7868719	US8944859
US9543667	US9368982
CA2869845	CA2857863
US9496726	CA2677283
CA2621644	MX338817

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of

this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.