



UPC Code : 078477675175

Country Of Origin : Mexico

WTD15-W

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Weather and Tamper-Resistant, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

Technical Information

Warranty

Horsepower Rating : 1/2 HP

Warranty : 10-Year Limited

AC Horsepower Rating

Amperage : 15 A

Dielectric Voltage : Withstands 3000 V minimum

Grounding : Self-Grounding

Horsepower Rating : 1/2 HP

Pole : 2

Temperature Rise : Max 30 °C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Electrical Specifications

Amperage : 15 A

Dielectric Voltage : Withstands 3000 V minimum

Flammability : Rated V-0 per UL 94

Grounding : Self-Grounding

Operating Temperature : -40°C to 75°C

Pole : 2

Temperature Rise : Max 30 °C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Body Material : PBT Polyester Blend

Face Material : PBT Polyester Blend

Flammability : Rated V-0 per UL 94

Ground Clips : Brass

Ground Contacts : 0.030" Brass

Grounding Screw : #8 hex head, triple drive Brass

Line Contacts : 0.030" Phosphor Bronze

Mounting Screws : Triple-Drive Plated Steel

Operating Temperature : -40°C to 75°C

Strap Material : Steel

Terminal Clamps : Brass

Terminal Screws : #8 Triple-Drive Brass

Material Specifications

Body Material : PBT Polyester Blend

Face Material : PBT Polyester Blend

Ground Clips : Brass

Mounting Screws : Triple-Drive Plated Steel

Product ID : Ratings are permanently marked on device

Strap Material : Steel

Terminal Accom. : #14 AWG - #10 AWG

Terminal Clamps : Brass

Terminal ID : Brass - Hot, Green - Ground, Silver - Neutral

Terminal Screws : #8 Triple-Drive Brass

Termination : Back or Side Wire

Wire Type : Stranded or Solid

Mechanical Specifications

Brand : Decora Plus

Color : White

Color / Feature : White

Device Type : Duplex Receptacle Outlet

Feature : Weather and Tamper-Resistant

Feature 2 : Weather and Tamper-Resistant

Feature 4 : Smooth Face

Grade : Heavy-Duty Industrial Specification Grade

Product ID : Ratings are permanently marked on device

Terminal Accom. : #14 AWG - #10 AWG

Terminal ID : Brass - Hot, Green - Ground, Silver - Neutral

Termination : Back or Side Wire

Wire Type : Stranded or Solid

Product Features

ANSI : C-73

Applicable Standards : UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

Brand : Decora Plus

Certification/Listing : cULus, NOM-ANCE

Color : White

Color / Feature : White

Device Type : Duplex Receptacle Outlet

Feature : Weather and Tamper-Resistant

Feature 2 : Weather and Tamper-Resistant

Feature 4 : Smooth Face

Grade : Heavy-Duty Industrial Specification Grade

Ground Contacts : 0.030" Brass
Grounding Screw : #8 hex head, triple drive Brass
Line Contacts : 0.030" Phosphor Bronze

RoHS : RoHS Compliant

Standards & Certifications

ANSI : C-73

Applicable Standards : UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

Certification/Listing : cULus, NOM-ANCE

RoHS : RoHS Compliant

Patents*

CA2483480	US6743029
CA2621644	US7355117
CA2624409	US7820909
CA2677283	US7868719
CN200880004760.2	US8242362
MX257790	US8684771
MX321216	

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

