

Compression F-Connector

APPLICATION

The Leviton Compression F-Connector is used in video applications such as CATV and satellite. Its radial-compression design provides a more secure termination on Series 6 Quad Shield Cable than the traditional hex-crimp design. For fast installation, terminate using a compression tool that provides a compression stroke of .22" for a finished connector length of 1.06"



SPECIFICATION

The Compression F-Connector shall be constructed with brass and a tin finish. It shall feature a radial-compression design, providing 360-degree electrical continuity. The connector shall be able to withstand greater than 40 lbs pull force and maintain ≤ -0.2 dB up to 1 GHz (typical). The return loss shall be ≥ -30 dB up to 1 GHz. The Compression F-Connector shall have RFI shielding of -85 dB (typical).

FEATURES

- Compatible with compression tool that provides a compression stroke of .22" for a finished connector length of 1.06"

DESIGN CONSIDERATIONS

- Includes plastic guide pin to determine when cable is properly seated inside the connector
- Comes in packs of 100 pieces

PHYSICAL SPECIFICATIONS

Dimensions:	See page two
Materials:	Tin-plated brass
Cable Applications:	< 20 lbs max insertion
Cable Interface:	> 40 lbs pull force
Insertion Loss:	≤ -0.2 dB up to 1 GHz typical
Return Loss:	≥ -30 dB up to 1 GHz typical
RFI Shielding:	-85 dB typical (60% bonded foil) > 70dB to 1GHz
Environmental Range:	-40 °F to 140 °F

COUNTRY OF ORIGIN


China

WARRANTY INFORMATION


For a copy of Leviton product warranties, visit www.leviton.com/warranty.

ELECTRONIC FILES

For CAD files, typical specs, or technical drawings (.DXF, .DWG), visit www.leviton.com.



End View



Side View

40985-CPF

PART NUMBERS

Description	Part No.
Compression F-Connector, 100-pack	40985-CPF

Leviton Network Solutions
 2222 - 222nd St. SE
 Bothell, WA 98021-4416

Asia / Pacific
 T +1.631.812.6228
 E infoasean@leviton.com

Canada
 T +1.514.954.1840
 E pcservice@leviton.com

Caribbean
 T +1.954.593.1896
 E infocaribbean@leviton.com

China
 T +852.2774.9876
 E infochina@leviton.com

Colombia
 T +57.1.743.6045
 E infocolombia@leviton.com

tel 1-800-824-3005
 tel +1-425-486-2222
 appeng@leviton.com
 www.leviton.com

Europe
 T +44.0.1592.772124
 E customerserviceeu@leviton.com

Mexico
 T +52.55.5082.1040
 E lsamarketing@leviton.com

Middle East & Africa
 T +971.4.247.9800
 E lmeinfo@leviton.com

South Korea
 T +82.2.3273.9963
 E infokorea@leviton.com