

3" Vertical Manager Ring

APPLICATION

3" wide, vertical distribution ring for equipment rack cords/cables. Mounts on side of rack, providing two separate distribution rings for front and rear cable routing. Optional interbay tie bracket (49261- BKT).



SPECIFICATION

Vertical manager rings shall mount on the side of a standard equipment rack and provide two separate distribution rings for front and rear cable management. The rear rings shall be 3" wide x 4.5" deep and provide the capacity to manage and store 180 cords/cables. The front rings shall be 3" x 6" and provide the capacity to manage and store 250 cords/cables. The vertical manager rings shall be capable of securing adjacent racks to one another with an optional interbay tie bracket. The rings shall have edges with a radius to protect cables from nicks and tears. The bracket material shall be .075" steel and the ring shall be 3/16" x 3/8" steel with black powder coat finish. The manufacturer shall provide a one-year limited product warranty and 15 year product performance guarantee. The manufacturer shall provide a limited lifetime warranty against defects in material and workmanship, and an application guarantee when installed as part of a certified system.

FEATURES

- Rings have edges with a radius to protect cable from nicks or wear.

COUNTRY OF ORIGIN

USA

DESIGN CONSIDERATIONS

- Specify this component as your primary vertical management for racks when used in combination with horizontal manager panels 49253-BCM or 49253-LPM.
- Specify this component as interbay vertical management (between racks) to distribute large volumes of patch cords when used with horizontal manager panels 49252-PCM. Note: These panels include vertical management more suitable to routing interbay patch cords (on the same rack).
- Allow for 3" rack spacing on center in multi-bay rack arrangements.
- Use 3-5 rings per side for adequate containment of patch cord and station cable bundles. Place rings on both sides of rack for more balanced patch cord distribution.
- Include one interbay tie bracket 49261-BKT to secure each ring to adjacent rack.

INSTALLATION NOTES

- Temporarily install two rings, at top and bottom, between racks before securing racks to the floor.
- Adjust ring locations to meet as-built arrangement of equipment, patch panels, and horizontal wire manager panels.
- Attach one interbay tie bracket 49261-BKT to secure each ring to adjacent rack.

STANDARDS COMPLIANCE

- UL Listed

MECHANICAL SPECIFICATIONS

Dimensions:	3" W x 4.5" D
Capacity:	180 cables or patch cords (.25" O.D., 4-pair, UTP cable)
Materials:	3/16" x 3/8" radius-edged steel, black powder coat finish
Front Ring:	
Dimensions:	3" W x 6" D
Capacity:	250 cables or patch cords (.25" O.D. 4-pair, UTP cable)
Materials:	3/16" x 3/8" radius-edged steel, black powder coat finish
Mounting Bracket:	
Materials:	12 gauge steel, black powder coat finish
Mounting:	Two #12-24 pilot-point screws are included.

PRODUCT SPECIFICATIONS

49260-MR3




WARRANTY INFORMATION

- One-year limited product warranty and 15-year performance guarantee are standard.
- Product and performance warranties are extended to a Lifetime as part of Leviton's Certified Cabling System.

ELECTRONIC FILES

For CAD files, typical specs, or technical drawings (.DXF, .DWG), visit leviton.com.

49260-MR3



PART NUMBER

Description	Part No.
3" Wide Vertical Manager Ring	49260-MR3

NETWORK SOLUTIONS GLOBAL HEADQUARTERS

Bothell, WA, USA | leviton.com/ns
(800) 824 3005 / +1 (425) 486 2222 | appeng@leviton.com

NETWORK SOLUTIONS EUROPEAN HEADQUARTERS

Glenrothes, UK | leviton.com/ns/emea
+44 (0) 1592 772124 | customerserviceeu@leviton.com

Leviton is dedicated to designing, developing and manufacturing sustainable high-performance structured cabling and speciality cabling solutions. Network Solutions products are available worldwide in over 100 countries. Visit us online to learn more.