

Commercial Downlight Comparison Chart

		Retrofits		New Construction			
							
		LBR Retrofit Downlight	LDNRV Downlight	LBR New Construction Downlight	LDN Downlight	LDN Switchable Downlight	LDN Cylinders
Focus	Stock	✓		✓	✓	✓	
	Specification		✓		✓		✓
Features / Performances	Aperture Sizes	4", 6", 8", 10", and 12"	4", 5", 6", 7", 8", 9" and 10"	4", 6", 8", and 10"	3", 4", 6", and 8"	4", 6", and 8"	4", 6", and 8"
	Installation	Install-from-below	Install-from-below	Mounting frame	Mounting frame	Mounting frame	Pendant, surface and wall mount
	Cutoff	55° cutoff to source	55° cutoff to source	55° cutoff to source	55° cutoff to source	55° cutoff to source	55° cutoff to source
	LPW (Max)	Up to 114 LPW	Up to 102 LPW	Up to 114 LPW	Up to 102 LPW	Up to 114 LPW	Up to 102 LPW
	Lumens (Max)	Switchable: up to 5,000LM	Up to 12,000LM	Switchable: up to 5,000LM	Up to 20,000LM	Switchable: up to 5,000LM	Up to 20,000LM
	CCTs	Switchable: 3000K - 5000K	2700/3000/3500/4000/5000K	Switchable: 3000K - 5000K	2700/3000/3500/4000K	Switchable: 3000K - 5000K	2700/3000/3500/4000K
	SensorSwitch™	✓	✓		4" and 6"	✓	
	nLight® Wired	✓	✓	✓	✓	✓	✓
	nLight® Air	✓	✓	✓	✓	✓	✓
	Emergency Battery Backup	✓		✓	✓	✓	
	Wet Location Listed	✓	✓	✓	✓	✓	✓