

505712 – Next Gen 5-MSP 25-Ft Cord

1/6 hp utility pump, 115 V, 25' cord, manual operation

Item: 505712

Model: Next Gen 5-MSP 25-Ft Cord

Ratings

HP	0.17 hp
Frequency	60 Hz
Phase	Single-Phase
Amps - Full Load	5 A
Amps - Starting	6.4 A
Full Load Watts	380 W
Volts	115 VAC
Cord Length	25 ft
Lead Length	25 ft
Motor Type	Submersible
Continuous Duty	Yes
Thermal Overload Protection	Yes
Protection [IP]	IP68
Maximum Flow Rate - 60Hz	25 gpm / 1500 gph
Minimum Flow Rate - 60Hz	4.17 gpm / 250 gph
Shut-Off	26 ft
Minimum Head - 60Hz	1.31 ft
Shut Off Height - 60Hz	26.3 ft
Stages	1
Max Solid Handling Size	0.13 "
Switch Type	Manual
Motor Cooling	Water

Liquid

Max Fluid Temperature	120 °F
-----------------------	--------

Materials of Construction

Pump Base Material	Plastic
Pump Body Material	Aluminum
Pump Volute Material	Nylon
r Type	Semi-open

Motor Shaft End Material	Stainless Steel
Intake Screen Material	Nylon
Top Bearing Type	Sleeve
Bottom Bearing Type	Sleeve Bearing
Seal Material	Viton Retainer
Seal Type	Viton

Installation

Discharge Thread	FNPT
Discharge Type	Threaded - FNPT
Discharge	1 "
Product Length	6.1 "
Product Width	4.29 "
Product Height	8.07 "
Pump Length	6.1 "
Product Weight	7.75 lb
Product Weight w/ Pack	8.25 lb
Carton Length	7.28 "
Carton Width	6.3 "
Carton Height	9.45 "

Other

Accessories Included	3/4" GHT garden hose adapter
Electrical Agency Approvals	UL
Standard Warranty	12 Months
	Warranty Terms and Conditions Link