INDIRECT WATER HEATERS

4 STANDARD MODELS

40 TO 119 GALLONS

BULBWELL

DENT RESISTANT JACKET

GLASS LINED STEEL TANK AND COIL

WELDED CONSTRUCTION

RELIEF VALVE INCLUDED

6 YEAR LIMITED WARRANTY



GLASS LINED INDIRECT WATER HEATERS





NO ONE **BRINGS IT ALL** TOGETHER LIKE LOCHINVAR

Lochinvar is the industry leader that other leading companies call upon for the most advanced and efficient water heating products in the world. For that reason, Lochinvar is trusted to go beyond the call of duty to find a solution for every project, no matter the size. You will not find a water heating company that works harder or cares more.

That's why no one brings it all together quite like Lochinvar.

GLASS LINED INDIRECT GIT MODELS DIMENSIONS AND SPECIFICATIONS





The "Hot Water Outlet" connection is Female NPT. All other connections are Male NPT.

Model Number	A	В	D	G	н		lydronic Coil Conn. Size		estic Water nn. Size Outlet	Ship. Wt. (lbs.)
GIT040	40"	23-2/3"	30"	21-2/3"	9-1/4"	3-3/4"	1"	1″	1-1/4"	165
GIT050	48"	23-2/3"	38-3/4"	27-1/3"	9-1/4"	3-3/4"	1"	1"	1-1/4"	200
GIT080	63-1/2"	23-2/3"	54-1/2"	32"	9-1/4"	2-3/4"	1"	1-1/2"	1-1/2"	250
GIT119	63-3/4"	29-1/2"	53-1/3"	33″	9-1/4"	3-1/2"	1"	1-1/2"	1-1/2"	320

	Potable	Standby	First	Continuous	1st Hour	HEAT SOURCE			
Model Number	Water Volume (Gallons)	Loss (°F/Hr)	Draw Gals.	Draw (GPH)	Rating (GPH)	Coil Volume (Gallons)	Min Coil Load (Btu/Hr)	Min Flow (GPM)	Friction Loss (Ft. Hd.)
GIT040	40.0	1.0	30	137	167	1.6	96,000	14.0	5.7
GIT050	50.0	1.3	45	182	227	1.9	133,000	14.0	5.8
GIT080	70.0	1.2	57	262	319	2.4	175,000	14.0	8.9
GIT119	115.0	0.5	95	294	389	2.8	197,000	14.0	11.0

Notes: These ratings were obtained with a heat source output rate and heat source flow rate shown in the table above. Other results shall be obtained under different conditions. Includes tank sensor for use with Lochinvar Heating Boiler.

Optional thermostat available for use with other boiler models.







