

SPECIFICATION SHEET

BREEZELUX 4x10

WALL AND CEILING SUPPLY VENT

DETAILS

Designed for 10" x 4" duct openings
Magnetic access
Flush-mount design
Removable panel
Compatible with 1/2" and 5/8" thick drywall
CFM Airflow at 500 Core Velocity exceeds 66

FEATURES

Seamless integration with drywall ceiling or wall
Easy access for airflow adjustment
Moisture, mold, and water-resistant
Pre-primed surface ready for custom finishing
Innovative magnetic closure system
Non-flammable materials
Ideal for: Spaces requiring discreet air supply solutions

PRODUCT SPECIFICATIONS

Size: 13.5" x 7.5" x 0.5"
Frame material: Durable 24 gauge galvanized steel
Panel material: Triple fibre reinforced cement board
Finish: Pre-primed white
Installation method: Frame installation followed by panel attachment
Closure mechanism: Magnetic
Moisture resistance: Yes
Mold resistance: Yes
Water resistance: Yes
Drywall compatibility: 1/2" and 5/8" thick drywall
Application: Drywall ceilings and walls
Slot configuration: 13 straight vertical slots, each 3" x 5/16"

MATERIAL SPECIFICATIONS

Raw Material: Cement, fibres, quartz sand, non-hazardous fillers
Density: $1.0 < D \leq 1.2 \text{ g/cm}^3$
Asbestos Content: 100% asbestos-free
Fire Resistance: non-combustible
Water Absorption: $\leq 40\%$
Resistant Bending Strength: $\leq 10.5 \text{ MPa dry}$
Moisture Movement: 0.25 %
Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing

