

# SPECIFICATION SHEET

## CLIQUEELITE 24x8

COLD AIR RETURN WALL COVER

### DETAILS

Designed for 24" x 8" duct openings or wall cavities  
Magnetic access  
Flush-mount design  
Removable panel  
Compatible with 1/2" and 5/8" thick drywall  
CFM Airflow at 500 Core Velocity exceeds 445

### FEATURES

Seamless integration with wall  
Easy installation and access for maintenance  
Moisture, mold, and water-resistant  
Pre-primed surface ready for custom finishing  
Non-flammable materials  
Impact resistant  
Ideal for: Spaces requiring discreet air return solutions

### PRODUCT SPECIFICATIONS

Size: 28.5" x 12.5" x 0.5"  
Vent Cover Dimensions: 26" x 10"  
Fits into drywall opening: 26.25" x 10.25"  
Frame material: Durable 24 gauge galvanized satin coat steel  
Panel material: Triple fibre reinforced cement board  
Finish: Pre-primed white  
Installation method: Frame installation followed by panel attachment  
Closure mechanism: Magnetic (4 magnetic tabs on Vent Cover)  
Moisture resistance: Yes  
Mold resistance: Yes  
Water resistance: Yes  
Drywall compatibility: 1/2" and 5/8" thick  
Application: Walls only (high towards ceiling or low towards floor)  
Not suitable for ceiling installation  
Slot configuration: 33 straight horizontal vent slots, 7.375" x 0.32"

### MATERIAL SPECIFICATIONS

Raw Material: Cement, fibres, quartz sand, non-hazardous fillers  
Density:  $1.0 < D \leq 1.2 \text{ g/cm}^3$   
Asbestos Content: 100% asbestos-free  
Fire Resistance: non-combustible  
Water Absorption:  $\leq 40\%$   
Resistant Bending Strength:  $\leq 10.5 \text{ MPa}$  dry  
Moisture Movement: 0.25 %  
Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing

