

SPECIFICATION SHEET

CLIQUEELITE 30x8

COLD AIR RETURN WALL COVER

DETAILS

Designed for 30" x 8" duct openings or wall cavities
Magnetic access
Flush-mount design
Removable panel
Compatible with 1/2" and 5/8" thick drywall
CFM Airflow at 500 Core Velocity exceeds 471

FEATURES

Seamless integration with drywall
Easy installation and access for maintenance
Moisture, mold, and water-resistant
Pre-primed surface ready for custom finishing
Non-flammable materials
Impact resistant
Ideal for: Spaces requiring discreet air return solutions

PRODUCT SPECIFICATIONS

Size: 32" x 12.5" x 0.5"
Vent Cover Dimensions: 29.37" x 9.625"
Fits into drywall opening: 29.75" x 10.25"
Frame material: Durable 24 gauge galvanized satin coat steel
Panel material: Triple fibre reinforced cement board
Finish: Pre-primed white
Installation method: Frame installation followed by panel attachment
Closure mechanism: Magnetic (4 magnetic tabs on Vent Cover)
Moisture resistance: Yes
Mold resistance: Yes
Water resistance: Yes
Drywall compatibility: 1/2" and 5/8" thick
Application: Walls only (high towards ceiling or low towards floor)
Not suitable for ceiling installation
Slot configuration: 48 straight horizontal vent slots - 5.915" x 0.32"

MATERIAL SPECIFICATIONS

Raw Material: Cement, fibres, quartz sand, non-hazardous fillers
Density: $1.0 < D \leq 1.2 \text{ g/cm}^3$
Asbestos Content: 100% asbestos-free
Fire Resistance: non-combustible
Water Absorption: $\leq 40\%$
Resistant Bending Strength: $\leq 10.5 \text{ MPa}$ dry
Moisture Movement: 0.25 %
Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing

