

SPECIFICATION SHEET

SILHOUETASE 8x8

WALL & CEILING EXHAUST FAN COVER

DETAILS

Designed for 8" x 8" exhaust fan openings
Magnetic access for 6.125" x 6.125" accessible opening size
Flush-mount design
Removable panel
Compatible with 1/2" and 5/8" thick drywall
Over 14.36 square inches (92.64 square cm) of open vent area
Can be used as a Ceiling Exhaust Fan Cover or Air Return Vent
Suitable for both wall and ceiling installation

FEATURES

Seamless integration with ceiling or wall
Easy access for maintenance
Moisture, mold, and water-resistant
Pre-primed surface ready for custom finishing
Innovative magnetic closure system with 4 rare earth magnets
20 degree angled slots for directional venting and to hide a fan
Non-flammable materials
Fire Rated
Impact Resistant
Eco-Friendly Manufacturing and Non-Hazardous

PRODUCT SPECIFICATIONS

Size: 10.125" x 10.125" x 0.5"
Vent Cover Dimensions: 7.625" x 7.625"
Vented Opening Dimensions: 5.613" x 5.613"
Fits into drywall opening: 8" x 8"
Frame material: 24 gauge galvanized satin coat steel with beaded edge and adjustable diffuser
Panel material: Triple fibre reinforced cement board
Finish: Pre-primed white
Closure mechanism: Magnetic
Slot configuration: 8 angled horizontal slots, each 5.613" x 0.32"

INSTALLATION TIPS

Designed for 1/2" and 5/8" thick drywall
Screws on to the face of your drywall
Once finished seaming over the flange, the product is ready to be primed and painted to your wall/ceiling color
The insert comes primed white and ready for your paint color

MATERIAL SPECIFICATIONS

Raw Material: Cement, fibres, quartz sand, non-hazardous fillers
Density: $1.0 < D \leq 1.2 \text{ g/cm}^3$
Asbestos Content: 100% asbestos-free
Fire Resistance: non-combustible
Water Absorption: $\leq 40\%$
Resistant Bending Strength: $\leq 10.5 \text{ MPa}$ dry
Moisture Movement: 0.25 %
Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing

