

Product data sheet

Specifications



ClimaSys forced vent. IP54, 58m3/h, 24V DC, with outlet grille and filter G2

NSYCVF38M24DPF

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 58 m3/h
[Us] rated supply voltage	10...27.6 V
Input voltage	24 V DC

Complementary

Absorbed power	3.6 W
[In] rated current	0.18 A
Noise level < at	40...41 dB
Bearing type	Ball
Height	External: 137 mm
Width	External: 117 mm
Depth	External : 49 mm
Cut-out dimensions	92 x 92 mm
Net weight	0.23 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-10...70 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	29 Pa flow rate 0 m³/h
Connections - terminals	Cable
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template
Condition of use	Flow rates depends on the work point, see ProClima software Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	12.000 cm
Package 1 Length	14.500 cm
Package 1 Weight	280.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	28.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	12.190 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	66.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	85.000 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

EU RoHS Directive

Compliant with Exemptions

SCIP Number

61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

No

Image of product in real life situation

