

Product data sheet

Specifications



ClimaSys forced vent. IP54, 850m3/h, 230V, with outlet grille and filter
G2

NSYCVF850M230PF

Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 838 m3/h at 50 Hz Free flow rate with standard filter: 803 m3/h at 60 Hz
[Us] rated supply voltage	207...244 V
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	150 W 50 Hz 195 W 60 Hz
[In] rated current	0.65 A 50 Hz 0.85 A 60 Hz
Noise level < at	75...76 dB
Bearing type	Ball
Height	External: 336 mm
Width	External: 316 mm
Depth	External : 162 mm
Cut-out dimensions	291 x 291 mm
Net weight	4.1 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-15...60 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	170 Pa flow rate 0 m³/h
Connections - terminals	Terminal block
IP degree of protection	IP54

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template
Condition of use	Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Overfrequent filter replacement should be avoided Filter must be cleaned and replaced regularly Surrounding environment must be relatively clean

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.000 cm
Package 1 Width	32.000 cm
Package 1 Length	34.000 cm
Package 1 Weight	4.386 kg
Unit Type of Package 2	P12
Number of Units in Package 2	24
Package 2 Height	110.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	116.000 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

EU RoHS Directive

Compliant with Exemptions

SCIP Number

61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

No

Image of product in real life situation

