

**NIBCO**

1516 Middlebury Street

Elkhart, IN 46516-4740

Phone: 574.295.3000 • **Fax:** 800.234.0557**Email:** info@nibco.com • **Web site:** www.nibco.com**F-908-W - Check Valve - Iron, Fire Protection, Horizontal Swing**

The cast iron check valve features flanged end connections for easy installation. The swing check valve includes a renewable rubber disc and bronze seat ring. Swing checks may be installed in horizontal positions (or vertical with flow moving up). The check valve is recommended for automatic fire sprinkler systems and is UL/ULC listed and FM approved. Please refer to NIBCO technical data sheets, chemical resistance guides and catalogs for engineering and installation information. Choose NIBCO®

+ n



Material Number	UPC Code	Valve Size	Connection Type	Description	Turns/Operation
<u>NHDX00E</u>	039923702487	2 1/2	F -- Flanged	F908W 2 1/2 FLG UL/FM CK CAST IRON	Non-Manual
<u>NHDX00F</u>	039923702494	3	F -- Flanged	F908W 3 FLG UL/FM CK CAST IRON	Non-Manual
<u>NHDX00H</u>	039923702500	4	F -- Flanged	F908W 4 FLG UL/FM CK CAST IRON	Non-Manual
<u>NHDX00J</u>	039923702517	5	F -- Flanged	F908W 5 FLG UL/FM CK CAST IRON	Non-Manual
<u>NHDX00K</u>	039923702524	6	F -- Flanged	F908W 6 FLG UL/FM CK CAST IRON	Non-Manual
<u>NHDX00L</u>	039923702531	8	F -- Flanged	F908W 8 FLG UL/FM CK CAST IRON	Non-Manual
<u>NHDX00M</u>	039923702548	10	F -- Flanged	F908W 10 FLG UL/FM CK CAST IRON	Non-Manual

Material Number	UPC Code	Valve Size	Connection Type	Description	Turns/Operati
<u>NHDX00N</u>	039923702555	12	F -- Flanged	F908W 12 FLG UL/FM CK CAST IRON	Non-Manual