

# AQUA-JET PE-4710

## IRON PIPE SIZED (ID) NSF LISTED WATER PIPE

Oil Creek Plastics, Inc. pressure rated pipe is manufactured from PE-4710 High Density Polyethylene and meets or exceeds all requirements of ASTM D2239, NSF Listed-Standards 14 and requirements of NSF Standard 61 and AWWA C901.

| SIZE | I.D. | MINIMUM WALL | WEIGHT PER 100' | MAX. PSI @73.4°F | COIL LENGTHS |
|------|------|--------------|-----------------|------------------|--------------|
|------|------|--------------|-----------------|------------------|--------------|

### SIDR-15 125 PSI

|        |       |      |      |     |         |
|--------|-------|------|------|-----|---------|
| 3/4"   | .824  | .060 | 7.4  | 125 | 100/400 |
| 1"     | 1.049 | .070 | 10.6 | 125 | 100/300 |
| 1-1/4" | 1.380 | .092 | 18.5 | 125 | 100/300 |
| 1-1/2" | 1.610 | .107 | 25.1 | 125 | 100/250 |
| 2"     | 2.067 | .138 | 41.1 | 125 | 100/200 |
| 3"     | 3.068 | .205 | 89.5 | 125 | 100/200 |

### SIDR-11.5 160 PSI

|        |       |      |      |     |         |
|--------|-------|------|------|-----|---------|
| 1/2"   | .622  | .060 | 5.8  | 160 | 100/400 |
| 3/4"   | .824  | .072 | 9.0  | 160 | 100/400 |
| 1"     | 1.049 | .091 | 14.2 | 160 | 100/300 |
| 1-1/4" | 1.380 | .120 | 24.5 | 160 | 100/300 |
| 1-1/2" | 1.610 | .140 | 33.1 | 160 | 100/250 |
| 2"     | 2.067 | .180 | 54.2 | 160 | 100/200 |

### SIDR-9 200 PSI

|        |       |      |      |     |          |
|--------|-------|------|------|-----|----------|
| 3/4"   | .824  | .092 | 11.5 | 200 | 100/400  |
| 1"     | 1.049 | .117 | 18.5 | 200 | See Note |
| 1-1/4" | 1.380 | .153 | 31.5 | 200 | 100/300  |
| 1-1/2" | 1.610 | .179 | 43.0 | 200 | 100/250  |
| 2"     | 2.067 | .230 | 70.4 | 200 | 100/200  |

### SIDR-7 250 PSI

|        |       |      |      |     |          |
|--------|-------|------|------|-----|----------|
| 3/4"   | .824  | .118 | 15.2 | 250 | 100/400  |
| 1"     | 1.049 | .150 | 24.3 | 250 | See Note |
| 1-1/4" | 1.380 | .197 | 41.6 | 250 | 100/300  |
| 1-1/2" | 1.610 | .230 | 56.4 | 250 | 100/250  |
| 2"     | 2.067 | .295 | 92.4 | 250 | 100/200  |

Note: 1" 200 PSI - 250 PSI — stocked in 100, 200, 300, 400, 500, 600 ft. lengths.

1" SIDR-9 200 PSI and SIDR-7 250 PSI — available in Blue.

| SIZE | NOMINAL O.D. | NOMINAL I.D. | MINIMUM WALL | WEIGHT PER 100' | COIL LENGTHS |
|------|--------------|--------------|--------------|-----------------|--------------|
|------|--------------|--------------|--------------|-----------------|--------------|

### SDR-9 AQUA-JET WATER SERVICE TUBING (CTS) COPPER TUBE SIZED (OD) 250 PSI

|        |       |       |      |      |         |
|--------|-------|-------|------|------|---------|
| 3/4"   | .875  | .671  | .097 | 10.3 | 100/500 |
| 1"     | 1.125 | .865  | .125 | 16.8 | 100/500 |
| 1-1/4" | 1.375 | 1.060 | .153 | 25.0 | 100/300 |
| 1-1/2" | 1.625 | 1.253 | .181 | 35.0 | 100/300 |
| 2"     | 2.125 | 1.637 | .236 | 59.7 | 100/300 |

**All SDR-9 CTS available in Black or Blue.**

Aqua-Jet Tubing meets ASTM D2737, NSF Listed-Standards 14 and requirements of NSF Standard 61 and AWWA C901.

Aqua-Jet Tubing may be joined by compression type fittings specifically designed for CTS polyethylene. (Not for use with insert fittings and clamps.)



Potable water



# OIL CREEK PLASTICS

## IPS (OD) WATER PIPE PE-4710

### AQUA-PLUS/AQUA-JET/GEOTHERMAL (OD)

Oil Creek Plastics, Inc. outside diameter-controlled water pipe is manufactured from PE-4710 high-density polyethylene resin and meets or exceeds all requirements of ASTM D3035 and is NSF Listed-Standards 14 and requirements of NSF Standard 61 and AWWA C901.

| SIZE           | O.D.  | MINIMUM WALL | WEIGHT PER 100' | PSI RATING |
|----------------|-------|--------------|-----------------|------------|
| <b>DR-13.5</b> |       |              |                 |            |
| 1/2"           | .840  | .062         | 7.2             | 160        |
| 3/4"           | 1.050 | .078         | 11.0            | 160        |
| 1"             | 1.315 | .097         | 16.8            | 160        |
| 1-1/4"         | 1.660 | .123         | 26.4            | 160        |
| 1-1/2"         | 1.900 | .141         | 34.4            | 160        |
| 2"             | 2.375 | .176         | 53.0            | 160        |
| 3"             | 3.500 | .259         | 115.2           | 160        |
| 4"             | 4.500 | .333         | 190.4           | 160        |
| 6"             | 6.625 | .491         | 413.3           | 160        |
| <b>DR-11</b>   |       |              |                 |            |
| 1/2"           | .840  | .076         | 8.4             | 200        |
| 3/4"           | 1.050 | .095         | 12.9            | 200        |
| 1"             | 1.315 | .120         | 20.0            | 200        |
| 1-1/4"         | 1.660 | .151         | 31.4            | 200        |
| 1-1/2"         | 1.900 | .173         | 40.9            | 200        |
| 2"             | 2.375 | .216         | 63.9            | 200        |
| 3"             | 3.500 | .318         | 138.6           | 200        |
| 4"             | 4.500 | .409         | 229.3           | 200        |
| 6"             | 6.625 | .602         | 496.8           | 200        |
| <b>DR-9</b>    |       |              |                 |            |
| 1/2"           | .840  | .093         | 9.9             | 250        |
| 3/4"           | 1.050 | .117         | 15.3            | 250        |
| 1"             | 1.315 | .146         | 23.5            | 250        |
| 1-1/4"         | 1.660 | .184         | 37.2            | 250        |
| 1-1/2"         | 1.900 | .211         | 48.7            | 250        |
| 2"             | 2.375 | .264         | 76.3            | 250        |
| 3"             | 3.500 | .389         | 165.7           | 250        |
| 4"             | 4.500 | .500         | 273.7           | 250        |
| 6"             | 6.625 | .736         | 593.0           | 250        |

Other DR pipe and pressure rating available upon request.

