

AQUA-JET PE-4710

IRON PIPE SIZED (ID) NSF LISTED WATER PIPE

Oil Creek Plastics, Inc. pressure rated pipe is manufactured from PE-4710 High Density Polyethylene and meets or exceeds all requirements of ASTM D2239, NSF Listed-Standards 14 and requirements of NSF Standard 61 and AWWA C901.

SIZE	I.D.	MINIMUM WALL	WEIGHT PER 100'	MAX. PSI @73.4°F	COIL LENGTHS
SIDR-19 100 PSI					
1"	1.049	.060	9.1	100	100/300
1-1/4"	1.380	.073	14.3	100	100/300
1-1/2"	1.610	.085	19.4	100	100/250
2"	2.067	.109	32.3	100	100/200

SIDR-15 125 PSI					
3/4"	.824	.060	7.4	125	100/400
1"	1.049	.070	10.6	125	100/300
1-1/4"	1.380	.092	18.5	125	100/300
1-1/2"	1.610	.107	25.1	125	100/250
2"	2.067	.138	41.1	125	100/200
3"	3.068	.205	89.5	125	100/200

SIDR-11.5 160 PSI					
1/2"	.622	.060	5.8	160	100/400
3/4"	.824	.072	9.0	160	100/400
1"	1.049	.091	14.2	160	100/300
1-1/4"	1.380	.120	24.5	160	100/300
1-1/2"	1.610	.140	33.1	160	100/250
2"	2.067	.180	54.2	160	100/200

SIDR-9 200 PSI					
3/4"	.824	.092	11.5	200	100/400
1"	1.049	.117	18.5	200	See Note
1-1/4"	1.380	.153	31.5	200	100/300
1-1/2"	1.610	.179	43.0	200	100/250
2"	2.067	.230	70.4	200	100/200

SIDR-7 250 PSI					
3/4"	.824	.118	15.2	250	100/400
1"	1.049	.150	24.3	250	See Note
1-1/4"	1.380	.197	41.6	250	100/300
1-1/2"	1.610	.230	56.4	250	100/250
2"	2.067	.295	92.4	250	100/200

Note: 1" 200 PSI - 250 PSI — stocked in 100, 200, 300, 400, 500, 600 ft. lengths.

1" SIDR-9 200 PSI and SIDR-7 250 PSI — available in Blue.

SIZE	NOMINAL O.D.	NOMINAL I.D.	MINIMUM WALL	WEIGHT PER 100'	COIL LENGTHS
SDR-9 AQUA-JET WATER SERVICE TUBING (CTS) COPPER TUBE SIZED (OD) 250 PSI					
3/4"	.875	.671	.097	10.3	100/500
1"	1.125	.865	.125	16.8	100/500
1-1/4"	1.375	1.060	.153	25.0	100/300
1-1/2"	1.625	1.253	.181	35.0	100/300
2"	2.125	1.637	.236	59.7	100/300

All SDR-9 CTS available in Black or Blue.

Aqua-Jet Tubing meets ASTM D2737, NSF Listed-Standards 14 and requirements of NSF Standard 61 and AWWA C901.

Aqua-Jet Tubing may be joined by compression type fittings specifically designed for CTS polyethylene. (Not for use with insert fittings and clamps.)



NSF-pw

Potable water

