GAS FURNACES

80% | 95% | 96%





SEE PAGE 2 FOR **SPECIFICATIONS** ON THE **95% & 96%** FURNACE



When the weather gets chilly, you'll get comfortable, consistent heating—and you can also be confident these furnaces are built for durable performance over the long haul.

80% SINGLE STAGE UPFLOW HORIZONTAL

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J801X045AU3SAA	80%	45,000	Upflow/Horizontal Right/Left	34.5 x 14.5 x 28
J801X054AU3SAA	80%	54,000	Upflow/Horizontal Right/Left	34.5 x 14.5 x 28
J801X072BU4SAA	80%	72,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J801X072CU5SAA	80%	72,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J801X090BU4SAA	80%	90,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J801X090CU5SAA	80%	90,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J801X108CU5SAA	80%	108,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J801X126DU5SAA	80%	126,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28

80% SINGLE STAGE DOWNFLOW

J801X054AD3SAA	80%	54,000	Downflow	34.5 x 14.5 x 28
J801X072BD4SAA	80%	72,000	Downflow	34.5 x 17.5 x 28
J801X090BD4SAA	80%	90,000	Downflow	34.5 x 17.5 x 28
J801X108CD5SAA	80%	108,000	Downflow	34.5 x 21 x 28
 J801X126DD5SAA	80%	126,000	Downflow	34.5 x 24.5 x 28

- All furnace models feature a standard silicon nitride igniter
- Furnace models feature aluminized steel heat exchangers to conduct heat quickly and increase durability
- Oxbox furnaces are built for flexibility to suit varied installations
- Furnaces are fully convertible to either natural gas or propane, making them suitable for use in any area
- Galvanized steel cabinets resist corrosion
- D FER compliant



GAS FURNACES

80% | 95% | 96%





95% SINGLE STAGE UPFLOW HORIZONTAL

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J951X038BU4SAA	95%	38,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J951X054BU4SAA	95%	54,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J951X072CU5SAA	95%	72,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J951X090CU5SAA	95%	85,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J951X108DU5SAA	95%	108,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28
J951X120DU5SAA	95%	120,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28

95% 2-STAGE VARIABLE SPEED UPFLOW HORIZONTAL

J952V060BUVSAA	95%	60,000	Upflow/Horizontal Right/Left	34.5 x 17.5 x 28
J952V080CUVSAA	95%	80,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J952V100CUVSAA	95%	100,000	Upflow/Horizontal Right/Left	34.5 x 21 x 28
J952X120DU5SAA	95%	120,000	Upflow/Horizontal Right/Left	34.5 x 24.5 x 28

Our innovative 1-5-10 no-registration warranty gives you maximum peace of mind. Plus, every piece of equipment is warranted to the home, not the homeowner-providing an extra measure of coverage when it comes time to sell.

WARRANTIES AVAILABLE:

1 Year: Complete Replacement ONLY COMPRESSORS, COILS, OR HEAT EXCHANGER FAILURE

5 Years: Standard Parts Warranty 10 Years: Compressor Replacement

96% 2-STAGE VARIABLE SPEED DOWNFLOW

J962V060BDVSAA	96%	60,000	Downflow	34.5 x 17.5 x 28
J962V080CDVSAA	96%	80,000	Downflow	34.5 x 17.5 x 28
J962V100CDVSAA	96%	100,000	Downflow	34.5 x 17.5 x 28
J962V115DDVSAA	96%	115,000	Downflow	34.5 x 17.5 x 28

For installation in SCAQMD only: These furnaces do not meet the SCAQMD Rule 1111 14 ng/J NOx emission limit and are only eligible for installation in high altitude (4,200 feet and above) or propane applications and are subject to a mitigation fee of up to \$450 USD. These furnace is not eligible for the Clean Air Furnace Rebate Program: www.CleanAirFurnaceRebate.com

Questions? Go to OXBOXHVAC.COM for more information.

