



Legrand

Heavy-Duty Decorator Spec Grade Receptacles, Back & Side Wire, 20A, 250V,
Ivory
Part No. 268521



Heavy-Duty Decorator Spec Grade Duplex Receptacle Back & Side Wire 20amp 250volt
Brown

Features & Benefits

Corrosion-resistant, plated steel strap locked into assembly to prohibit strap from bending away from body.

Heavy-duty compact design for easier installation and long lasting performance.

Impact-resistant nylon face.

Side and internal screw-pressure-plate back wire accepts #14 - #10 AWG solid or stranded wire.

Tri-drive terminal and mounting screws.

For covering patents, see www.legrand.us/patents.

One-piece, brass, triple-wipe power contacts for lasting retention.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Terminal compartments isolated from each other for positive conductor containment.

All devices fit standard #26 opening wall plate.

Auto-ground clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

Specifications

General Info

Color Ivory

UPC Number 785007786392

Country Of Origin Mexico

Product Line Pass & Seymour

Application Sector Commercial

Standard UL498, cUL CSA

Listing Agencies / 3rd Party Agencies

cULus Listed Yes

cULus ListingNumber 140596

Technical Information

Number of Poles Double Pole

| | |
|----------------|-------|
| Voltage | 250 V |
|----------------|-------|

| | |
|-------------------|--------------------|
| Connection | Back and side wire |
|-------------------|--------------------|

| | |
|----------------------------|--------------------------|
| Dielectric Strength | Withstands 2000V minimum |
|----------------------------|--------------------------|

| | |
|---------------------------|---|
| Temperature Rating | Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact |
|---------------------------|---|

| | |
|------------------|-----------|
| Wire Size | #14 - #10 |
|------------------|-----------|

| | |
|------------------------|---|
| Number of Wires | 3 |
|------------------------|---|

| | |
|---------------------------------|-----------------------|
| Environmental Conditions | Flammability: UL94 V2 |
|---------------------------------|-----------------------|
