



# Legrand PlugTail® Connectors, Right Angle, Stranded, 6"

Part No. PTR6STR



PlugTail® Connectors Right Angle Stranded 6" For detailed PlugTail® information, visit our PlugTail® Headquarters.

## Features & Benefits

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.

Large brass contacts snugly terminate on device blade terminals.

Pre-stripped connector leads fasten to conductors, easier than standard pigtails.

Available in any wire length up to 25 inches, use Configurable Solutions to order.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

## Specifications

### General Info

UPC Number	785007044546	Country Of Origin	China
Product Line	Pass & Seymour	Application Sector	Commercial
Standard	cULus UL498		

### Listing Agencies / 3rd Party Agencies

cULus Listed	Yes	cULus ListingNumber	140596
--------------	-----	---------------------	--------

### Technical Information

Number of Poles	Double Pole	Dielectric Strength	Withstands 2000V minimum
Temperature Rating	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact	Wire Size	PlugTail™ Connector: #12 AWG, THHN, copper conductor, 6" leads, stripped, stranded, for use with PlugTail Receptacles only
Number of Wires	3	Environmental Conditions	Flammability: UL94 V2