



# 3-1/2 in. EMT Raintight Compression Connector, Uninsulated

By RACO  
Catalog # 2944RT



3-1/2 in. EMT Raintight Compression Connector, Uninsulated

## Features

- Steel construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Marked with "Wet Location" for easy inspection
- cULus
- Available in trade sizes of 1/2 in. through 4 in.
- Installed knockout seal

## Specifications

|                          |                      |
|--------------------------|----------------------|
| Buy American Compliant   | Contact Manufacturer |
| Certified Listed         | cULus Listed         |
| Environmental Conditions | Wet Location         |
| EU RoHS Indicator        | Contact Manufacturer |
| Buy America(n) Qualified | Contact Manufacturer |
| Industry Standard(s)     | UL 514B              |

## Configuration

|                |             |
|----------------|-------------|
| Connector Type | Compression |
|----------------|-------------|

## Dimensions

|        |          |
|--------|----------|
| Length | 3.827 in |
|--------|----------|

|            |                              |
|------------|------------------------------|
| Trade Size | 3-1/2 in                     |
| Weight     | 2.178 lb.                    |
| Height     | 4.8 in                       |
| Width      | 4.585 in                     |
| Dimensions | 3.827 in x 4.585 in x 4.8 in |

## General

|                 |              |
|-----------------|--------------|
| Conduit Type    | EMT          |
| Insulation Type | Uninsulated  |
| Fitting Type    | Connectors   |
| UPC             | 050169501023 |
| Material        | Steel        |

## Logistics

|                       |     |
|-----------------------|-----|
| Minimum Pack Quantity | 1   |
| Pallet Quantity       | 448 |
| Carton Quantity       | 1   |

## Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)