



Raintight Compression Couplings - Steel



Applications

- For use in wet locations to couple two ends of EMT conduit
- RACO® Raintight Steel EMT compression fittings are designed to comply with new UL Raintight test requirements and to comply with the requirements of the 2014 NEC 358.42 and 314.15



Couplings

Product Features

- All steel construction ensures mechanical protection for the raceway
- Available in 1/2" to 4" trade sizes
- Zinc-electroplate finish
- All fittings are marked "Wet Locations" to allow inspecting authorities to immediately determine that the installation is up to code
- No need to disassemble the fitting prior to installation. RACO Raintight Steel EMT compression fittings are designed to come out of the carton ready to install directly on the conduit. No time wasted loosening compression nuts
- No special tools required. Install these fittings like any other Steel EMT compression fitting. No need for a torque wrench to insure proper installation

Compression Couplings - Steel

Catalog #	Trade Size	Unit Carton Qty.	Ship Carton Qty.
2922RT	1/2"	50	250
2923RT	3/4"	25	125
2924RT	1"	15	75
2925RT	1-1/4"	—	20
2926RT	1-1/2"	—	10
2928RT	2"	—	10
2950RT	2-1/2"	—	1
2952RT	3"	—	1
2954RT	3-1/2"	—	1
2956RT	4"	—	1

Compliance

- Standard 514B
C22.2 # 18
UL Listed E195970

See end of section (Pg B89) for detailed drawings »