



Compression Connectors - Steel



Applications

- For use when bonding EMT conduit to a box or enclosure
- RACO® 1/2" to 4" connectors provide concrete-tight connections
- RACO® compression connectors are suitable for applications above 600V



Insulated Throat
Connectors



Uninsulated Throat
Connectors

Product Features

- All steel construction ensures mechanical protection for the raceway
- All components are zinc-electroplated for corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for attractive presentation

Compliance

1/2" - 2"

- Standard 514B
C22.2 # 1
UL Listed E195970

Compression Connectors - Steel

Insulated Catalog #	Uninsulated Catalog #	Trade Size	Unit Carton Qty.	Ship Carton Qty.	Bar Code
2912	2902	1/2"	50	500	—
2912-8	2902-8	1/2"	1	25	
2913	2903	3/4"	25	250	—
2913-8	2903-8	3/4"	1	20	
2914	2904	1"	25	100	—
2914-8	2904-8	1"	1	10	
2915	2905	1-1/4"	5	25	—
2916	2906	1-1/2"	—	20	—
2918	2908	2"	—	20	—
2960	2940	2-1/2"	—	5	—
2962	2942	3"	—	1	—
2964	2944	3-1/2"	—	1	—
2966	2946	4"	—	1	—

See end of section (Pg B88) for detailed drawings »