



1-1/4 in. Liquidtight Straight Connector, Uninsulated

By RACO
Catalog # 3405

1-1/4 in. Liquidtight Straight Connector, Uninsulated

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Buy American Compliant Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL 514B
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2

Dimensions



Length	2.438 in
Trade Size	1-1/4 in
Weight	0.635 lb.
Height	2.188 in
Width	2.438 in
Dimensions	2.438 in x 2.438 in x 2.188 in

General

Conduit Type	Liquidtight
Insulation Type	Uninsulated
Fitting Type	Connectors
UPC	050169034057
Material	Steel/Malleable Iron

Logistics

Minimum Pack Quantity	10
Pallet Quantity	2700
Carton Quantity	10

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)