



2-1/2 in. Liquidtight Straight Connector, Uninsulated

By RACO
Catalog # 3410

2-1/2 in. Liquidtight Straight Connector, Uninsulated

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Buy American Compliant Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Environmental Conditions	Wet Location
EU RoHS Indicator	Yes
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL 514B
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2

Dimensions



Length	3.938 in
Trade Size	2-1/2 in
Weight	2.6 lb.
Height	3.563 in
Width	3.938 in
Dimensions	3.938 in x 3.938 in x 3.563 in

General

Conduit Type	Liquidtight
Insulation Type	Uninsulated
Fitting Type	Connectors
UPC	050169034101
Material	Steel/Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	972
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)