



## 3 in. Liquidtight Straight Connector, Uninsulated

By RACO  
Catalog # [3412](#)

3 in. Liquidtight Straight Connector, Uninsulated

### Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

### Specifications

|                                         |                                                                                                                                                     |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Buy American Compliant Certified Listed | Contact Manufacturer <ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>                                            |
| Environmental Conditions                | Wet Location                                                                                                                                        |
| EU RoHS Indicator                       | Yes                                                                                                                                                 |
| Buy America(n) Qualified                | Contact Manufacturer                                                                                                                                |
| Industry Standard(s)                    | UL 514B                                                                                                                                             |
| Hazardous Rating(s)                     | <ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul> |

### Dimensions



|            |                              |
|------------|------------------------------|
| Length     | 4.75 in                      |
| Trade Size | 3 in                         |
| Weight     | 3.6 lb.                      |
| Height     | 3.813 in                     |
| Width      | 4.75 in                      |
| Dimensions | 4.75 in x 4.75 in x 3.813 in |

### General

|                 |                      |
|-----------------|----------------------|
| Conduit Type    | Liquidtight          |
| Insulation Type | Uninsulated          |
| Fitting Type    | Connectors           |
| UPC             | 050169034125         |
| Material        | Steel/Malleable Iron |

### Logistics

|                       |     |
|-----------------------|-----|
| Minimum Pack Quantity | 1   |
| Pallet Quantity       | 640 |
| Carton Quantity       | 1   |

### Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)