



1-1/2 in. 90 Degree Liquidtight Connector, Uninsulated

By RACO
Catalog # 3426

1-1/2 in. 90 Degree Liquidtight Connector, Uninsulated

Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal and preventing pullouts
- RACO liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO liquidtight connector assures continuity of ground
- All steel/iron components are zinc electroplated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- 3/8 in. to 1 in. Steel, 1-1/4 in. to 4 in. Malleable Iron bodies and nuts
- Additional sizes available

Specifications

Buy American Compliant Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
EU RoHS Indicator	Yes
Buy America(n) Qualified Industry Standard(s)	Contact Manufacturer UL 514B



Hazardous Rating(s)

- Class I, Division 2
- Class II Division 1 & 2
- Class III, Division 1 & 2

Dimensions

Length	2.813 in
Trade Size	1.5 in
Weight	1.36 lb.
Height	5.063 in
Width	2.813 in
Dimensions	2.813 in x 2.813 in x 5.063 in

General

UPC	050169034262
Material	Steel/Malleable Iron

Logistics

Minimum Pack Quantity	5
Pallet Quantity	1200
Carton Quantity	5

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)