



**NEW
PRODUCT**

VAMP-X

Condensate Pump



BENEFITS

- Easy and quick installation
- Minimal space requirement:
standing at just 1 inch height
- Quiet operation
- External reservoir
with optical level sensing
for maximum flexibility
- Manufactured in Switzerland

Part No
3004239

DISCOVER
THE PRODUCT
ONLINE



REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally



DATA SHEET

Property	Value
Maximum flow rate	22 l/h (6 GPH)
Maximum discharge height	15 m (49 ft)
Maximum suction lift	2 m (6.6 ft)
Maximum horizontal run	75 m at 0 m head and 0 m suction (246 ft at 0 ft head and 0 ft suction)
Pump type	Diaphragm pump
Electrical ratings	100-240 VAC, 50/60 Hz, 6 W, Protection Class II
Alarm relay rating	Normally-closed, failsafe 250 VAC, 5 A or 30 VDC, 5 A
Ingress protection	Fully potted IP67 / cable connector IP44
Operating temperature	3 °C – 40 °C (37 °F – 104 °F)
Water temperature	3 °C – 40 °C (37 °F – 104 °F)
Storage temperature	-20 °C – 70 °C (-4 °F – 158 °F)
Noise level	< 20 dB(A)
Compliance	CE

Spare parts and accessories:

VAMP-X-SENSOR	3004243
POSABLE-HOSE/4 (with filter)	4689088
KIT-4087 (Star tube & Anti-Siphon)	3004087
STAR-TUBE-600 (15 m / 50 ft)	3004186
PVC-TUBE (¼" / 6 mm, 30 m / 98 ft)	4679160
INLINE-FILTER	4678597
CP-INSTALLATION-CABLE	4689089
HSG-4065/4 (Anti-Siphon)	3004065

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally