

KJ-1750 WATER JETTER

CLEAR 11/4" TO 4" (32 TO 102 MM) DRAIN LINES

The RIDGID® KJ-1750 water jetter effectively cleans lines with an actual working pressure of 1750 psi (121 bar) and a flow of 1.4 gpm (5.3 lpm). Two levels of pulse are standard and let you easily navigate difficult bends or traps. Its 2 HP (1491 W) motor draws a maximum of 17 amps which requires a 20 amp, 115 V circuit. Purpose built with quality components, the KJ-1750 features a duplex pump with a corrosion-resistant, forged brass head. The control valve lets you quickly and easily adjust water pressure.

► POWERFUL PRESSURE

Actual working pressure of 1750 psi (121 bar) and flow of 1.4 gpm (5.3 lpm)

► ELECTRICAL REQUIREMENTS

2 HP (1491 W) motor draws a maximum of 17 amps which requires a 20 amp, 115 V circuit

► EASY OPERATION

Thrust propels the hose down the line

► CLEAN BEYOND THE DRAIN

Optional power washer package cleans cables, tools and heavily soiled equipment

| CATALOG No. | MODEL No. | DESCRIPTION |
|----------------|--------------|--|
| 62687 | KJ-1750 | KJ-1750 Jetter with Dual Pulse: H-41, H-42, and H-44 $^1\!/s"$ (3 mm) NPT Nozzles, H-51 and H-52 $^1\!/s" \times 50'$ (3 mm \times 15 m) Sink Trap Hose, Nylon Storage Bag, Nozzle Cleaning Tool |
| 62697 | KJ-1750-C | Same as above with: H-30 Cart, ½" \times 110' (13 mm \times 34 m) Jet Hose |
| 67332 | _ | 62687 with: H-10 Cart, $1\!\!4\text{"}\times100\text{'}$ (6 mm \times 30 m) Trap Hose |