






Baseboard Radiators




Runtal's Baseboard style is ideal for those desiring a low profile. As a retrofit, Runtal baseboard is a natural replacement for fin-tube or cast iron. In these cases, it is often easiest to use the existing piping and simply order the appropriate lengths. Depending upon the heat output, or the desired design "look", Runtal will supply baseboard styles ranging from 1 to 4 tubes high.

				
With Fins*				
Model No.	VLX 7/7	VLX 14/14	VLX 21/21	VLX 28/28
Height	2.8"	5.8"	8.6"	11.5"
Depth	2"	2"	2"	2"
BTUH/ft.				
Output @ 180°F:	380	610	790	950



				
No Fins*				
Model No.	VX 7	VX 14	VX 21	VX 28
Height	2.8"	5.8"	8.6"	11.15"
Depth	2"	2"	2"	2"
BTUH/ft.				
Output @ 180°F:	160	290	430	570



Available in lengths from 20 to 354 inches (in 2" increments).

*Runtal baseboards are offered with and without fins. When hung, visually they look similar. Finned units offer a higher convective component and as a result nearly double the output of comparable non-finned units.



In Stock Baseboard UF Series




Runtal offers 2, 3 and 4 panels high baseboards in white for immediate delivery in 2', 2.5', 3', 3.5', and from 4'-14' in even foot increments. All stock baseboards have multiple tappings (AB) that allow for all types of bottom and side piping connections (See piping configuration AB on page 13, Table 3). Stock baseboards may be special ordered in any of the other nine standard colors with a two-week delivery.

runtal Wall Panels



Runtal's Wall Panel style radiators are ideal for placement under windows or on walls where floor space is at a premium. When placed under windows, wall panels help eliminate cold spots and drafts while allowing curtains to hang to the floor. Wall panel radiators are available in a variety of heights and widths to suit most any need.



With Fins*

Model No.	VLX 35/35	VLX 42/42	VLX49/49	VLX 56/56	VLX 63/56	VLX 70/56
Height	14.4"	17.2"	20.2"	23.1"	26.1"	29.0"
Depth	2"	2"	2"	2"	2"	2"
BTUH/ft.						
Output @ 180°F:	1260	1460	1650	1840	1950	2050

No Fins*

Model No.	VX 35	VX 42	VX 49	VX 56	VX 63	VX 70
Height	14.4"	17.2"	20.2"	23.1"	26.1"	29.0"
Depth	2"	2"	2"	2"	2"	2"
BTUH/ft.						
Output @ 180°F:	710	860	1010	1150	1300	1450

Available in lengths from 20 to 354 inches (in 2" increments).

Additional heights (up to 24 tubes high or 69-3/4") available upon request.

*Runtal wall panels are offered with and without fins. When hung, visually they look similar. Finned units offer a higher convective component and as a result nearly double the output of comparable non-finned units.

www.runtalnorthamerica.com



In Stock Wall Panels UF Series



Runtal offers 2 wall panels (6 and 8 panels) in 2', 3', and 4' lengths in white for immediate delivery. All stock wall panels have multiple tapplings (AB) that allow for all types of bottom and side piping connections (See piping configuration AB on page 13, Table 3). Stock wall panels may be special ordered in any of the other nine standard colors with a two-week delivery.