

LS 300 UV-RESISTANT LINE SET TAPE

TYPICAL APPLICATIONS

- For taping outdoor HVAC components

PRODUCT FEATURES

- UV-resistant line set tape
- Easy to unwind
- Can be applied in a variety of temperature ranges and used in humid conditions
- Recommended for Residential Use only

CONSTRUCTION

Backing: BOPP film black with white print

Adhesive: Acrylic-based adhesive

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	35 oz/in width	3.83 N/10 mm
Elongation	180%	180%
Service Temperature Range	-35 F to 210 F	-37 C to 99 C
Tensile	37 lbs/in width	64.8 N/10 mm
Thickness	2.85 mils	0.07 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

