

PC 609 Duck Pro® by Shurtape®



PC 609 DUCK PRO® BY SHURTAPE® PROFESSIONAL GRADE, CO-EXTRUDED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For use in the HVAC industry to repair thermal insulation and seal metal ductwork
- Can be used in the manufactured housing industry to seam bottom boards and for patching, seaming and sealing
- Used for general purpose packaging, bundling, holding, wrapping and waterproofing
- Also used for asbestos and mold remediation

PRODUCT FEATURES

- Professional grade, co-extruded duct tape
- Cold-temperature adhesion
- Excellent holding power with good conformability
- Easy to unwind and tear
- Waterproof backing

CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	64 oz/in width	7.00 N/10 mm
Elongation	23%	23%
Service Temperature Range	25 F to 200 F	-4 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	10.0 mils	0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

