

## PC 622 PREMIUM GRADE STUCCO DUCT TAPE

### TYPICAL APPLICATIONS

- For protecting window and door frames during stucco applications
- Used in high performance motorsports
- For heavy duty bundling, holding and splicing

### PRODUCT FEATURES

- Premium grade cloth duct tape
- Excellent holding power
- High tensile strength
- Conformable
- Waterproof backing

### CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

### STANDARD WIDTHS

1.41 in; 1.88 in; 2.83 in  
36 mm; 48 mm; 72 mm

### STANDARD LENGTH

60.1 yd  
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

Tested in accordance with UL 723

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLORS



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	54 oz/in width	5.91 N/10 mm
Elongation	11%	11%
Service Temperature Range	50 F to 200 F	10 C to 93 C
Tensile	45 lbs/in width	78.8 N/10 mm
Thickness - Nominal	12.5 mils	0.32 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

