




## Table of Contents

PRODUCT	PAGE #
<b>RWD</b>	
Mounting Devices	C-54
Accessories/Replacement Parts	C-54
<b>Direct Mount</b>	
Accessories	C-54
<b>All Pneumatic Products</b>	
Pneumatic Spring Clamp	C-55
<b>185/195 Receiver-Controllers</b>	
Tools	C-55
Replacement Scales	C-55
Connectors/Restrictors	C-56
Termination Strips	C-56
Replacement Parts	C-56
<b>184 Temperature Transmitters</b>	
Restrictors	C-57
Wells/Well Mounting Kit	C-57
Bulb Shields	C-57
Replacement Parts	C-57
<b>141 Air Velocity Transmitters</b>	
Restrictors	C-57
Probes	C-57






## Accessories & Service Kits

C-54

Controllers & Transmitters

		Description	Product Group	Quantity	Part No.
RWD		<b>Housing Enclosure.</b> Protective enclosure used for wall mounting.	RWD	1	<b>ARG62.21</b>
		<b>Housing Barrier.</b> For use with housing enclosure above.	RWD	1	<b>ARG100</b>
		<b>Time Clock.</b>	RWD	1	<b>SEH62.1U</b>
		<b>24/120 Vac Transformer (30 VA).</b>	RWD	1	<b>SEM62.2U</b>
		<b>Controller Software Tool.</b>	RWD	1	<b>125-3481</b>
Direct Mount		<b>Remote Setting Unit.</b>	Driver Mount Controllers	1	<b>BSG21.1</b>
		<b>Temperature Controller Software Tool.</b>	Driver Mount Controllers	1	<b>ACS100.1U</b>
		<b>Immersion Well.</b> 1/2" NPT x 6" long	Driver Mount Controllers	1	<b>ARG150U</b>

## Accessories & Service Kits

All Pneumatic Products		Description	Product Group	Quantity	Part No.
		<b>Pneumatic Spring Clamp.</b>	All	1	531-833
185/195 Receiver-Controllers	 195-098	<b>185/195 Receiver-Controller Simulator.</b> Used for setup and calibration. Comes complete with a carrying case and the following parts:			
		• One gauge/switch assembly	185, 195	1	195-098
		• Two gauge/switch assemblies	185, 195	1	195-099
		• Three gauge/switch assemblies	185, 195	1	195-100
		• Single gauge/switch assembly (without a case)	185, 195	1	195-108
		<b>Receiver-Controller Calibration Slide Rule.</b> Used to calculate proportional band and control point authority.	185, 195	1	153-054
		<b>Calibration Card.</b> Shows transmitter pressures for various analog ranges to assist in calibration.	185, 195	1	144-022
		<b>Setpoint Dial Sheets.</b> Direct Acting and Reverse Acting.	195	4 Sheets	195-130
		<b>English Units</b>	<b>Metric Units</b>	<b>Scale ID</b>	
		-40 to +120°F	-40 to +50°C	A	
		50 to 100°F	10 to 38°C	B	
		80 to 240°F	26 to 117°C	C	
		20 to 80% RH	-18 to +38°C	D	
		0 to 100°F	1 to 58°C	E	
		35 to 135°F	0 to 750 Pa	F	
		0 to 3 W.G.	0 to 3.75 kPa	G	
		0 to 15 W.G.	20 to 80% RH	H	
		0 to 0.5 W.G.	0 to 125 Pa	J	
		Blank 10 divisions	Blank 9 divisions	K (DA)	
		Blank 16 divisions	Blank 11 divisions	K (RA)	
		-0.05 to ±0.2" W.G.	-12.5 to +50 Pa	L	
		-0.5 to +0.5" W.G.	-125 to +125 Pa	M	
		0 to 10" W.G.	0 to 2.5 kPa	N	
	Blank 20 divisions	Blank 15 divisions	P		
	0 to 50 psi	0 to 345 kPa	R		
	50 to 150°F	10 to 66°C	S		
	40 to 240°F	4 to 116°C	T		
	-40 to +160°F	-40 to +71°C	V		
	30 to 190°F	-1 to +88°C	W		

### Ordering Notes

- Add Scale ID as suffix to Part No.
- Indicate English or Metric units.






C-55

Controllers & Transmitters











## Accessories & Service Kits

C-56

Controllers & Transmitters

185/195 Receiver-Controllers		Description	Product Group	Quantity	Part No.
		<b>Receiver-Controller Restriction Kit.</b> Includes three input restriction plates, one pilot relay restriction plate, gaskets, and two screws.	195	1 Kit	<b>195-066</b>
		<b>Receiver-Controller Connector Kit.</b> Includes two plug-in connector assemblies, one 3-barb input connector assembly. <ul style="list-style-type: none"> <li>• Multiple-Input</li> <li>• Single-Input</li> </ul>	195	1 Kit	<b>195-067</b>
		<b>Termination Strip.</b> For numbered ports 1 through 10, straight through connections for 1/4" (6 mm) OD polyethylene tubing.	195	1	<b>195-082</b>
		<b>Pressure Gauge.</b> Dual Scale 0 to 30 psig (0 to 200 kPa ) 12" NPT male thread (back)	184, 195	1	<b>142-0373</b>
		<b>In-Line Air Filter.</b>	195	1	<b>908-033</b>

## Accessories & Service Kits

184 Temperature Transmitters		Description	Product Group	Quantity	Part No.
		<b>Restrictor Tees.</b> 40 scim for 1/4" (6 mm) OD plastic. Required for 195 Receiver-Controller only when total transmitter line is greater than 300' (91 m) long.	184	Package of 5	<b>184-114</b>
		<b>In-line Restrictors.</b> 40 scim (11 ml/s)	184	Package of 5	<b>184-117</b>
		<b>Well Mounting Bracket Kit.</b>	184	1	<b>184-105</b>
		<b>Copper Well.</b> 1/4" D x 4" L (6 mm D x 102 mm L)	184	1	<b>184-119</b>
		<b>Stainless Steel Well.</b> 1/4" D x 4" L (6 mm D x 102 mm L)	184	1	<b>184-118</b>
		<b>Outdoor Bulb Shield.</b> 9" (229 mm) L	184	1	<b>134-084</b>
		<b>3-1/2" Enthalpy Receiver Gauge.</b> 16 to 40 BTU/lb. (37 to 93 kJ/kg)	184	1	<b>142-0424</b>
141 Air Velocity Transmitters		<b>Restrictor Tees.</b> 40 scim for 1/4" (6 mm) OD plastic. Required for 195 Receiver-Controller only when total transmitter line is greater than 300' (91 m) long.	184	Package of 5	<b>184-114</b>
		<b>Static Pressure Sensor Probe.</b>	141	1	<b>269-062</b>
		<b>Static Pressure Probe Kit.</b>	SW269	1	<b>189-142</b>













