

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 12 1-INCH SPACES ALLOWING MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

| General technical data                               |                                                        |
|------------------------------------------------------|--------------------------------------------------------|
| configuration of the busbars                         | ALUMINUM BUS                                           |
| number of circuits in a trunking unit                | 24                                                     |
| phase number                                         | 1                                                      |
| suitability for operation                            | RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION |
| Electricity                                          |                                                        |
| ampacity                                             | 125 A                                                  |
| voltage between phase and Ground (GND) rated value   | 120 V                                                  |
| voltage between phase and phase rated value          | 240 V                                                  |
| Model                                                |                                                        |
| product brand name                                   | SIEMENS                                                |
| product sub brand name                               | LOAD CENTERS                                           |
| product type designation                             | PLUG-ON NEUTRAL READY STANDARD SERIES                  |
| special product feature                              | GREY TRIM                                              |
| Mechanical Design                                    |                                                        |
| number of modular width units for installation width | 12                                                     |
| General product approval                             |                                                        |
| certificate of suitability                           | UL                                                     |

last modified:

7/9/2021 

