

METAL STUD INSULATOR

»» 558-M SERIES

PipeEye™

SPECIFICATION

Sioux Chief 558-M series PipeEye™ metal stud insulators shall be used where necessary to insulate and isolate CTS copper, PEX or CPVC supply lines from contact with metal studs or galvanized brackets in residential or commercial applications. Insulators shall be designed to fit 1¹¹/₃₂" diameter hole. 558-M23 series shall accept both 1/2" and 3/4" CTS tube. All insulators shall be IAPMO certified.

INSTALLATION

Requires 1¹¹/₃₂" hole size. Install tube through hole in stud or bracket, position grommet around tube. Push insert through the hole until the tabs click to lock insulator into place. Rotate insulator to adjust tube's position.

MATERIALS

Standard 558-M: High-density polyethylene (black and red)

Flame Retardant 558-MR: ABS flame-retardant (natural)

SAFE WORKING TEMPERATURE

Impact resistant to 0°F

Maximum temperature 160°F (continuous)


DIMENSIONS

	Tube Size	Grommet Diameter
558-M23	1/2" & 3/4" CTS	1.339
558-M4	1" CTS	1.343


ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



558-M23



558-M23



558-M4



Made in USA

Create Item Number

558-MA

e.g. **558-M23:** PipeEye metal stud insulator for 1/2" and 3/4" CTS pipe

MATERIAL & CTS SIZE A

- 23 = 1/2" and 3/4" CTS, black
- 23H = 1/2" and 3/4" CTS, red
- 23R = 1/2" and 3/4" CTS (glues-to-CPVC), natural
- 4 = 1" CTS, black
- 4H = 1" CTS, red
- 4R = 1" CTS (glues-to-CPVC), natural