

Valves Product  
**Compact Ball Valves (Regular Style)**



**Compact Ball Valves (Regular Style)**



Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi  
3" - 6" 150 psi  
Flanged 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)  
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply  
Rated for Vacuum Service

Socket/Threaded Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section  
for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

**PVC**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
<b>Socket Ends</b>					
1/2	2122-005 48.98	2132-005 55.17	10	80	210
3/4	2122-007 66.85	2132-007 68.48	10	0	210
1	2122-010 72.96	2132-010 81.91	10	0	210
1-1/4	2122-012 130.84	2132-012 145.47	6	0	210
1-1/2	2122-015 162.01	2132-015 169.25	5	0	210
2	2122-020 174.62	2132-020 196.19	6	0	210
3	2122-030 567.54	2132-030 637.59	1	4	211
4	2122-040 873.16	2132-040 1256.85	1	0	211
6 (Lever Handle)	2122-060 1133.94	2132-060 1632.23	1	0	211
6 (Tee Handle)	21226-060 1133.94	21326-060 1632.23	1	0	211

**Threaded Ends**

1/2	2121-005 48.98	2131-005 55.17	10	80	210
3/4	2121-007 66.85	2131-007 68.48	10	0	210

**PVC (continued)**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
<b>Threaded Ends</b>					
1	2121-010 72.96	2131-010 81.91	10	0	210
1-1/4	2121-012 130.84	2131-012 145.47	6	0	210
1-1/2	2121-015 162.01	2131-015 169.25	5	0	210
2	2121-020 174.62	2131-020 196.19	6	0	210
3	2121-030 567.54	2131-030 637.59	1	4	211
4	2121-040 873.16	2131-040 1256.85	1	0	211

**Flanged Ends**

1/2	2123-005 108.31	2133-005 115.39	1	8	210
3/4	2123-007 131.06	2133-007 136.23	1	8	210
1	2123-010 144.57	2133-010 153.49	1	8	210
1-1/4	2123-012 204.71	2133-012 219.27	1	8	210
1-1/2	2123-015 236.82	2133-015 247.96	1	4	210
2	2123-020 274.91	2133-020 296.27	1	0	210
3	2123-030 738.52	2133-030 808.59	1	0	211
4	2123-040 1089.29	2133-040 1472.97	1	0	211
6 (Lever Handle)	2123-060 2097.40	2133-060 2308.72	1	0	211
6 (Tee Handle)	21236-060 2097.40	21336-060 2308.72	1	0	211

**CPVC**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
<b>Socket Ends</b>					
1/2	2122-005C 54.25	2132-005C 60.35	10	80	212
3/4	2122-007C 71.56	2132-007C 80.46	10	0	212
1	2122-010C 89.48	2132-010C 100.57	10	0	212
1-1/4	2122-012C 181.07	2132-012C 201.07	6	0	212
1-1/2	2122-015C 223.67	2132-015C 235.16	5	0	212
2	2122-020C 237.20	2132-020C 266.51	6	0	212
3	2122-030C 721.71	2132-030C 804.97	1	4	213
4	2122-040C 1334.17	2132-040C 1498.94	1	0	213



Valves Product

**Compact Ball Valves (Regular Style) & Lab Ball Valves**

**Compact Ball Valves (Regular Style)**

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

**Socket Ends**

<b>6 (Lever Handle)</b>	2122-060C <b>2180.39</b>	2132-060C <b>2323.31</b>	1	0	213
<b>6 (Tee Handle)</b>	21226-060C <b>2180.39</b>	21326-060C <b>2323.31</b>	1	0	213

**Threaded Ends**

<b>1/2</b>	2121-005C <b>54.25</b>	2131-005C <b>60.35</b>	10	80	212
<b>3/4</b>	2121-007C <b>71.56</b>	2131-007C <b>80.46</b>	10	0	212
<b>1</b>	2121-010C <b>89.48</b>	2131-010C <b>100.57</b>	10	0	212
<b>1-1/4</b>	2121-012C <b>181.07</b>	2131-012C <b>201.07</b>	6	0	212
<b>1-1/2</b>	2121-015C <b>223.67</b>	2131-015C <b>235.16</b>	5	0	212
<b>2</b>	2121-020C <b>237.20</b>	2131-020C <b>266.51</b>	6	0	212
<b>3</b>	2121-030C <b>721.71</b>	2131-030C <b>804.97</b>	1	4	213
<b>4</b>	2121-040C <b>1334.17</b>	2131-040C <b>1498.94</b>	1	0	213

**Flanged Ends**

<b>1/2</b>	2123-005C <b>151.27</b>	2133-005C <b>157.39</b>	1	8	212
<b>3/4</b>	2123-007C <b>175.61</b>	2133-007C <b>184.51</b>	1	8	212
<b>1</b>	2123-010C <b>207.65</b>	2133-010C <b>218.78</b>	1	8	212
<b>1-1/4</b>	2123-012C <b>327.20</b>	2133-012C <b>347.29</b>	1	8	212
<b>1-1/2</b>	2123-015C <b>409.18</b>	2133-015C <b>421.82</b>	1	4	212
<b>2</b>	2123-020C <b>463.40</b>	2133-020C <b>492.71</b>	1	0	212
<b>3</b>	2123-030C <b>1109.68</b>	2133-030C <b>1192.96</b>	1	0	213
<b>4</b>	2123-040C <b>1733.46</b>	2133-040C <b>1898.23</b>	1	0	213
<b>6 (Lever Handle)</b>	2123-060C <b>3292.61</b>	2133-060C <b>3532.29</b>	1	0	213
<b>6 (Tee Handle)</b>	21236-060C <b>3292.61</b>	21336-060C <b>3532.29</b>	1	0	213

**Lab Ball Valves**



Socket/Threaded Valve Only



Valve & Adapters

Pressure Rating @ 73°F (23°C),  
Water  
1/8" - 3/8" 150 psi

Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings  
Apply

Rated for Vacuum Service

**Valve & Adapters includes:**

- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or FKM O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters

**Lab Valve - PVC**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

**Valve & Adapters Threaded Ends**

<b>1/4X1/4T</b>	1529-002A <b>56.64</b>	1539-002A <b>59.22</b>	1	25	218
<b>1/4X3/8T</b>	1529-002 <b>56.64</b>	1539-002 <b>59.22</b>	1	25	218

**Valve only Threaded Ends**

<b>1/4</b>	1521-002 <b>45.26</b>	1531-002 <b>50.42</b>	50	200	218
<b>3/8</b>	1521-003 <b>63.64</b>	1531-003 <b>70.56</b>	50	200	218

**Valve Only Female x Male Thread Ends**

<b>1/8</b>	152FM-001 <b>56.64</b>	153FM-001 <b>59.22</b>	25	200	218
<b>1/4</b>	152FM-002 <b>56.64</b>	153FM-002 <b>59.22</b>	25	200	218

**Valve only Socket Ends**

<b>1/4</b>	1522-002 <b>45.26</b>	---	50	200	218
<b>3/8</b>	1522-003 <b>63.64</b>	---	50	200	218