

Plug in relay, Type KP, tubular, 1 HP at 277 VAC, 10A resistive at 120 VAC, 8 pin, DPDT, 2 NO, 2 NC, 120 VAC coil

8501KPR12V20

Product availability: Stock - Normally stocked in distribution

facility

Price*: 47.58 USD

| Product range | 8501K |
|------------------------------|---------------------|
| Product type | Relay |
| Relay Type | General purpose |
| Mounting type | Socket |
| Contact composition | DPDT |
| [Uc] control circuit voltage | 120 V AC |
| Pilot light | No indicator |
| Manual operator | Without test button |

Complementary

| Horsepower rating | 1 hp 277 V AC 0.33 hp 120 V AC |
|---------------------------|--|
| Breaking capacity | 3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 277 V AC resistive control circuit UL 508 10 A 30 V DC resistive control circuit UL 508 |
| Maximum switching voltage | 300 V AC 30 V DC |
| Contact material | Silver alloy (AgNi) |
| Operating time | 20 ms - pick-up 20 ms - drop-out |
| Shape of pins | Tubular |
| For use with | 8501NR52 8501NR51 |

Environment

| Ambient temperature range - operational | -40131 °F (-4055 °C) |
|---|--------------------------------|
| Product certifications | UL Listed UL Recognized CSA CE |
| Height | 2.66 in (67.56 mm) |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Width | 1.4 in (35.56 mm) |
|-------|-------------------|
| Depth | 1.4 in (35.56 mm) |

Ordering and shipping details

| Category | 21141-8501 KP |
|-------------------|---------------|
| Discount Schedule | CP2 |
| GTIN | 785901147329 |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.70 in (4.318 cm) |
| Package 1 Width | 1.70 in (4.318 cm) |
| Package 1 Length | 3.00 in (7.62 cm) |
| Package 1 Weight | 4.80 oz (136.078 g) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 75 |
| Package 2 Height | 40.00 in (101.6 cm) |
| Package 2 Width | 36.00 in (91.44 cm) |
| Package 2 Length | 48.00 in (121.92 cm) |
| Package 2 Weight | 15.75 lb(US) (7.144 kg) |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 120 |
| Package 3 Height | 6.30 in (16.002 cm) |
| Package 3 Width | 6.00 in (15.24 cm) |
| Package 3 Length | 15.60 in (39.624 cm) |
| Package 3 Weight | 9.85 lb(US) (4.468 kg) |

Offer Sustainability


| Sustainable offer status | Green Premium product |
|----------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |

Product data sheet

8501KPR12V20


Dimensions Drawings

Approximate Dimensions



Connections and Schema

Connections and Wiring Diagrams



Recommended replacement(s)