

Product data sheet

Characteristics

HOM2448L125PQGC

Homeline, LC, 125 A, 120/240 V, 1 PH, MLO, PoN, 24 SP, N1, grd bar, quick grip

Product availability : Stock - Normally stocked in distribution facility



Price** : 344.00 USD



Main

Product or component type	Load Center
Marketing Trade Name	Homeline
Load center type	Main lugs
Line Rated Current	125 A
Number of spaces	24
Number of circuits	48
Enclosure Rating	NEMA 1 indoor
Included Options	Grounding bar 1)

Complementary

Short-circuit current	10 kA
Number of Tandem Breakers	24
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 6...AWG 2/0 aluminium AWG 6...AWG 1 copper
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	8Q
Height	26.02 in (661 mm)
Width	14.25 in (362 mm)
Depth	3.74 in (95 mm)
Tightening torque	5.65 N.m (50 lbf.in) AWG 6...AWG 1) 5.65 N.m (50 lbf.in) AWG 6...AWG 2/0)

Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL

Ordering and shipping details

Category	00045 - HOM LC&CVR, 12-42 CKT, NEMA1
Discount Schedule	DE3C
GTIN	00785901593553
Package weight(Lbs)	11.07 kg (24.41 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Under investigation