

Product data sheet

Characteristics

HOM816M200PFTRB

Homeline, LC, 150 A, 120/240 V, 1 PH, MB, PoN, 8 SP, N3R, surf, feed thru

Product availability : Stock - Normally stocked in distribution facility



Price** : 785.00 USD



Main

Product or component type	Load Center
Marketing Trade Name	Homeline
Load center type	Main breaker
Line Rated Current	200 A
Number of spaces	8
Number of circuits	16
Enclosure Rating	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Feed-thru lugs
Included Options	Circuit breaker 1) 2P 200 A 120/240 V AC main supply ready assembled Grounding bar 1) ready assembled

Complementary

Short-circuit current	22 kA
Number of Tandem Breakers	8
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 4...250 kcmil copper or aluminium
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	6R
Height	29.84 in (758 mm)
Width	14.76 in (375 mm)

Depth	4.53 in (115 mm)
-------	------------------

Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL E-6294

Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R
Discount Schedule	DE3C
GTIN	00785901973959
Package weight(Lbs)	15.72 kg (34.65 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations