

Product availability : Stock - Normally stocked in distribution facility



Price** : 102.00 USD



Main

Product	Load Center
Marketing Trade Name	QO
Cover type	Surface cover

Complementary

Load Center Type	Main lugs
Line Rated Current	60 A
Number of spaces	2
Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	4
Maximum Number of Tandem Breakers	2
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 14...AWG 4 aluminium/copper
Electrical Connection	Lugs
Grounding Bar	Neutral (factory installed)
Electrical connection	Lugs
Wiring configuration	3-wire
Busbar Material	Tin plated aluminium busbar
Enclosure Material	Non-metallic
Box number	1NM
Height	8.78 in (223 mm)
Width	6.54 in (166 mm)
Tightening torque	3.95 N.m (35 lbf.in) 0.00...0.01 in ² (2.08...5.26 mm ²) AWG 14...AWG 10) 3.95 N.m (35 lbf.in) 0.01...0.01 in ² (3.30...5.26 mm ²) AWG 12...AWG10) 4.52 N.m (40 lbf.in) AWG 8...AWG 4) 4.52 N.m (40 lbf.in) 0.01 in ² (8.36 mm ²) AWG 8...AWG 4)

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL listed

Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901328025
Package weight(Lbs)	0.64 kg (1.42 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------