



### Main


Range of product	8501R
Product or component type	Miniature Relay
Contacts material	Silver tin oxide
Switch function	DPDT
[Uc] control circuit voltage	24 V AC
Rated power in HP	0.33 120 V 0.5 240 V
Mounting support	Socket
Ambient air temperature for operation	-40...158 °F
Shape of pin	Spade
Product certifications	CE CSA RoHS UL recognized
Operating time	25 ms pick-up 20 ms drop-out
Local signalling	Green indicator on
Control type	Without
Product compatibility	8501NR42
Relay type	Standard

### Ordering and shipping details

Category	21143 - 8501 R
Discount Schedule	CP2
GTIN	00785901131335
Nbr. of units in pkg.	1
Package weight(Lbs)	8.999999999999997E-2

Country of origin	CN
-------------------	----

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1418 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------