

8536SEO1V02S

Non-Reversing Starter Size 3, 3-Pole, Melting Alloy Overload +Options

Product availability : Stock - Normally stocked in distribution facility



Price* : 1638.00 USD



Main

Product or component type	Starter
Range of product	S
Line Rated Current	90 A
Product certifications	UL listed CSA NEMA
Control circuit	Separate control circuit
Control type	No control units
NEMA degree of protection	Not rated (open device)
Rated power in HP	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	3
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3 Thermal Units
Height	11.1 in (282 mm)
Depth	6.5 in (165 mm)
Width	5.47 in (139 mm)

Ordering and shipping details

Category 21193 - 8502,36 SE,SF(NOT S*R,T,W)

Discount Schedule	CP1
GTIN	00785901788515
Nbr. of units in pkg.	1
Package weight(Lbs)	15.68
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------